

MIAMI-DADE COUNTY
 BUILDING CODE COMPLIANCE OFFICE (BCCO)
 PRODUCT CONTROL DIVISION
NOTICE OF ACCEPTANCE (NOA)
 PGT Industries
 1878 Technology Drive
 Nokomis, FL 34275

MIAMI-DADE COUNTY, FLORIDA
 METRO DADE FLAGLER BUILDING
 140 WEST PLAZA CENTER BLVD, SUITE 140
 MIAMI, FLORIDA 33135-1835
 (305) 375-3901 FAX: (305) 732-4339
 www.miamidade.gov/buildingcode

NOTICE OF ACCEPTANCE (NOA)
 PGT Industries
 1878 Technology Drive
 Nokomis, FL 34275

SCOPE:
 This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ). This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (to Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will bear the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High-Velocity Hurricane Zone.

DESCRIPTION: Series "FD-250" Outswing Aluminum French Door w/Sidelites - L.M.L.

APPROVAL DOCUMENT: Drawing No. 8009-11, titled "Alum. French Door & Side Lites, Impact", sheets 1 through 12 of 12, dated 12/23/04, with revision D dated 01/25/10, prepared by the manufacturer, signed and sealed by Robert L. Clark, P.E., having the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Division.

MINIMUM IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL: This NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION: This NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purpose shall automatically terminate this NOA. Failure to comply with any provision of this NOA shall be cause for termination and removal of NOA.

ADVERTISING: The NOA number provided by the Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the manufacturer or its distributor and shall be available for inspection at the job site at the request of the Building Official. This NOA is valid and remains NOA # 09-1828-19 and includes this page 1 and includes pages 2-1, 2-2 and 2-3, as well as approval document mentioned above.

The submitted documentation was reviewed by **Manuel Perez, P.E.**

NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

PGT Industries
NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS
 1. Manufacturer's drawings and sections.
 2. Drawing No. 8009-11, Sheets 1 through 12 of 12, titled "Alum. French Door & Side Lites, Impact", dated 12/23/04 with revision D dated 01/25/10, prepared by the manufacturer, signed and sealed by Robert L. Clark, P.E.

B. TESTS
 1. Test reports on: 1) Air Infiltration Test, 2) Uniform Static Air Pressure Test, 3) Water Resistance Test, 4) Forced Entry Test, per SFBFC 3603.2 (b) along with marked-up drawings and installation diagram of aluminum sliding glass door using a low alkaline glass with 710° laminated glass, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-5941, dated 05/20/09, signed and sealed by Julio E. Gonzalez, P.E.
 2. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94, 2) Uniform Static Air Pressure Test, per FBC, TAS 202-94, 3) Water Resistance Test, per FBC, TAS 202-94, 4) Large Missile Impact Test, per FBC, TAS 203-94, 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94, 6) Forced Entry Test, per FBC 241.1.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of aluminum doors of OXXX configuration, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-4921, dated 07/17/06, signed and sealed by Edmundo Largaespada, P.E.
 3. Test reports on: 1) Uniform Static Air Pressure Test, per FBC, TAS 202-94, 2) Large Missile Impact Test, per FBC, TAS 203-94, 3) Cyclic Wind Pressure Loading per FBC, TAS 203-94, 4) Forced Entry Test, per FBC 241.1.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of aluminum doors of OXXX configuration, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-4527, dated 02/10/05, signed and sealed by Edmundo Largaespada, P.E. (Submitted under NOA # 05-0419.03)
 4. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94, 2) Uniform Static Air Pressure Test, per FBC, TAS 202-94, 3) Water Resistance Test, per FBC, TAS 202-94, 4) Forced Entry Test, per FBC 241.1.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of aluminum doors of OXXX configuration, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-4528, dated 02/10/05, signed and sealed by Edmundo Largaespada, P.E. (Submitted under NOA # 05-0419.03)

C. CALCULATIONS
 1. Anchor verification calculations and structural analysis, complying with FBC 2007, dated 10/01/09, prepared, signed and sealed by Robert L. Clark, P.E. Complies with ASTM E1300-02/04

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

PGT Industries
NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

D. QUALITY ASSURANCE
 1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS
 1. Notice of Acceptance No. 09-0312.02 issued to D.I. DuPont DuPonts & Co., Inc. for their "DuPont Butacitec PVB Interlayer" dated 05/13/09, expiring on 12/11/10.
 2. Notice of Acceptance No. 06-0216.06 issued to Solvix Inc. for their "Saflex IIIIG Clear or colored interlayer" dated 05/04/06, expiring on 05/21/11.
 3. Notice of Acceptance No. 08-0528.08 issued to Solvix Inc. for their "Vanacea Composites Glass Interlayer" dated 7/17/05, expiring on 12/11/13.

F. STATEMENTS
 1. Statement letter of conformance, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 2. Statement letter of no financial interest, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 3. Laboratory compliance letter for Test Report No. FTL-4921, issued by Fenestration Testing Laboratory, Inc., dated June 26, 2006, signed and sealed by Edmundo Largaespada, P.E.
 4. Proposal No. 08-1891 issued by BCCO, dated January 26, 2009, signed by Ismael Chardas, P.E.

G. OTHER
 1. Notice of Acceptance No. 07-0103.02, issued to PGT Industries for their Series FD-250 Outswing Aluminum French Door w/Sidelites - L.M.L., approved on 03/15/07 and expiring on 02/24/10.

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

PGT Industries
NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

D. QUALITY ASSURANCE
 1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS
 1. Notice of Acceptance No. 09-0312.02 issued to D.I. DuPont DuPonts & Co., Inc. for their "DuPont Butacitec PVB Interlayer" dated 05/13/09, expiring on 12/11/10.
 2. Notice of Acceptance No. 06-0216.06 issued to Solvix Inc. for their "Saflex IIIIG Clear or colored interlayer" dated 05/04/06, expiring on 05/21/11.
 3. Notice of Acceptance No. 08-0528.08 issued to Solvix Inc. for their "Vanacea Composites Glass Interlayer" dated 7/17/05, expiring on 12/11/13.

F. STATEMENTS
 1. Statement letter of conformance, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 2. Statement letter of no financial interest, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 3. Laboratory compliance letter for Test Report No. FTL-4921, issued by Fenestration Testing Laboratory, Inc., dated June 26, 2006, signed and sealed by Edmundo Largaespada, P.E.
 4. Proposal No. 08-1891 issued by BCCO, dated January 26, 2009, signed by Ismael Chardas, P.E.

G. OTHER
 1. Notice of Acceptance No. 07-0103.02, issued to PGT Industries for their Series FD-250 Outswing Aluminum French Door w/Sidelites - L.M.L., approved on 03/15/07 and expiring on 02/24/10.

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

NOTES: OUTSWING IMPACT FRENCH DOOR(S) AND SIDE LITE(S)

1. GLAZING OPTIONS:
 A. 7/16" LAMI CONSISTING OF (1) LITE OF 3/16" ANNEALED GLASS AND (1) LITE OF 3/16" HEAT STRENGTHENED GLASS WITH AN .080 PVB INTERLAYER OF DUPONT BUTACITEC OR SAFLEX/KEEPSAFE MAXIMUM.
 B. 7/16" LAMI CONSISTING OF (2) LITES OF 3/16" HEAT STRENGTHENED GLASS WITH AN .080 PVB INTERLAYER OF DUPONT BUTACITEC OR SAFLEX/KEEPSAFE MAXIMUM.
 C. 7/16" LAMI CONSISTING OF (1) LITE OF 3/16" ANNEALED GLASS AND (1) LITE OF 3/16" HEAT STRENGTHENED GLASS WITH AN .075 VANCEVA INTERLAYER.
 D. 7/16" LAMI CONSISTING OF (2) LITES OF 3/16" HEAT STRENGTHENED GLASS WITH AN .075 VANCEVA INTERLAYER.
 E. 7/8" LAMI I.G. CONSISTING OF (1) LITE OF 3/16" TEMPERED GLASS OUTSIDE, 1/4" AIR SPACE AND (1) 7/16" LAMI GLASS ASSEMBLY INSIDE (3/16" .080 PVB, 3/16" HS).
 F. 7/8" LAMI I.G. CONSISTING OF (1) LITE OF 3/16" TEMPERED GLASS OUTSIDE, 1/4" AIR SPACE AND (1) 7/16" LAMI GLASS ASSEMBLY INSIDE (3/16" HS, .075 VANCEVA, 3/16" HS).
 G. 7/8" LAMI I.G. CONSISTING OF (1) LITE OF 3/16" TEMPERED GLASS OUTSIDE, 1/4" AIR SPACE AND (1) 7/16" LAMI GLASS ASSEMBLY INSIDE (3/16" HS, .075 VANCEVA, 3/16" HS).
 H. 7/8" LAMI I.G. CONSISTING OF (1) LITE OF 3/16" TEMPERED GLASS OUTSIDE, 1/4" AIR SPACE AND (1) 7/16" LAMI GLASS ASSEMBLY INSIDE (3/16" HS, .075 VANCEVA, 3/16" HS).

2. DESIGN PRESSURES: TABLE 1, SHEET 3.
 A. NEGATIVE DESIGN LOADS BASED ON TESTED PRESSURE AND GLASS TABLES ASTM E1300-02.
 B. POSITIVE DESIGN LOADS BASED ON WATER TEST PRESSURE AND GLASS TABLES ASTM E1300-02.

3. CONFIGURATION: X, O, XX, XO, OX, OXX, OOX, OXXO, OXXO, OR OXXX WHERE Q REPRESENTS EITHER THE NARROW JAMB OR FULL JAMB SIDE LITE. ANY TWO ADJACENT Q UNITS CAN BE EITHER TWO SINGLE, X DOORS OR A DOUBLE, XX DOORS BOTH USING EITHER THE STANDARD OR THE LOW-RISE SILL. THE FRENCH DOOR ASSEMBLY BEAM IS USED TO ASSEMBLE X, O, AND Q UNITS TO MAKE THE ABOVE CONFIGURATIONS.

4. ANCHORAGE: THE 33 1/3% STRESS INCREASE HAS NOT BEEN USED IN THE DESIGN OF THIS PRODUCT. FOR ANCHORAGE REQUIREMENTS SEE SHEETS 9 THRU 11.

5. SHUTTERS ARE NOT REQUIRED.

6. SEALANT: INSTALLATION SCREWS, FRAME AND PANEL CORNERS SEALED WITH CLEAR COLORED SEALANT. VERTICAL ASSEMBLY BEAM SEAMS SEALED ON THE INTERIOR AND EXTERIOR WITH CONTRACTOR'S SEALANT.

7. REFERENCES: TEST REPORTS: FTL-4911, FTL-4912, FTL-4915, FTL-4527, FTL-4528, FTL-4529, FTL-4530, FTL-4921 AND FTL-4941. ANSI/APA NDS-2005 FOR WOOD CONSTRUCTION. ADA-2008 ALUMINUM DESIGN MANUAL.

8. THIS PRODUCT HAS BEEN DESIGNATED AS TESTED TO COMPLY WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE, CURRENT EDITION INCLUDING THE HIGH VELOCITY HURRICANE ZONE (HVHZ).

NOA DRAWING MAP

TOPIC	SHEET
GENERAL NOTES	1
CONFIGURATIONS	1
GLAZING DETAILS	2
DESIGN PRESSURES	3
ELEVATIONS	4
VERT. SECTIONS	5
HORIZ. SECTIONS	6
PARTS LIST	7
EXTENSIONS	8-9
ANCHORAGE	10-12

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

PGT Industries
NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

D. QUALITY ASSURANCE
 1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS
 1. Notice of Acceptance No. 09-0312.02 issued to D.I. DuPont DuPonts & Co., Inc. for their "DuPont Butacitec PVB Interlayer" dated 05/13/09, expiring on 12/11/10.
 2. Notice of Acceptance No. 06-0216.06 issued to Solvix Inc. for their "Saflex IIIIG Clear or colored interlayer" dated 05/04/06, expiring on 05/21/11.
 3. Notice of Acceptance No. 08-0528.08 issued to Solvix Inc. for their "Vanacea Composites Glass Interlayer" dated 7/17/05, expiring on 12/11/13.

F. STATEMENTS
 1. Statement letter of conformance, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 2. Statement letter of no financial interest, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 3. Laboratory compliance letter for Test Report No. FTL-4921, issued by Fenestration Testing Laboratory, Inc., dated June 26, 2006, signed and sealed by Edmundo Largaespada, P.E.
 4. Proposal No. 08-1891 issued by BCCO, dated January 26, 2009, signed by Ismael Chardas, P.E.

G. OTHER
 1. Notice of Acceptance No. 07-0103.02, issued to PGT Industries for their Series FD-250 Outswing Aluminum French Door w/Sidelites - L.M.L., approved on 03/15/07 and expiring on 02/24/10.

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

Table 1. Maximum Design Pressures (psf)

Configuration	Width (in)	Allowed Glass Type	Height (in)					
			78 3/4" (8')	83 3/4" (7')	87 3/4"	91 3/4"		
French Door	X 37" (3')	A,E	+70.0	-80.0	+70.0	-80.0	+70.0	-80.0
		C,G	+100.0	-100.0	+100.0	-100.0	+100.0	-100.0
Full Jamb	36 11/16"	A,E	+70.0	-80.0	+70.0	-80.0	+70.0	-80.0
		C,G	+100.0	-100.0	+100.0	-100.0	+100.0	-100.0
Narrow Jamb	33 11/16"	A,B,E,F	+70.0	-80.0	+70.0	-80.0	+70.0	-80.0
		C,G	+100.0	-100.0	+95.3	-95.3	+91.4	-87.9
SideLite	36 11/16"	A,E	+70.0	-80.0	+70.0	-80.0	+70.0	-80.0
		C,G	+100.0	-100.0	+100.0	-100.0	+100.0	-100.0
SideLite	33 11/16"	A,B,E,F	+70.0	-80.0	+70.0	-80.0	+70.0	-80.0
		C,G	+100.0	-100.0	+95.3	-95.3	+91.4	-87.9
SideLite	30 11/16"	A,E	+70.0	-80.0	+70.0	-80.0	+70.0	-80.0
		C,G	+100.0	-100.0	+100.0	-100.0	+100.0	-100.0

Table 1a. Glass Type and Test Report Number

A - 7/16" LAMI (3/16" A, .080 PVB, 3/16" HS)	FTL-4311, 4312, 4315
B - 7/16" LAMI (3/16" HS, .080 PVB, 3/16" HS)	UPGRADE FTL-4311, 4312, 4315
C - 7/16" LAMI (3/16" A, .075 VANCEVA, 3/16" HS)	FTL-4527, 4528, 4529, 4530
D - 7/16" LAMI (3/16" HS, .075 VANCEVA, 3/16" HS)	UPGRADE FTL-4527, 4528, 4529, 4530
E - 7/8" LAMI I.G. (3/16" T, 1/4" AIR SPACE, 3/16" A, .080 PVB, 3/16" HS)	FTL-4311, 4312, 4315
F - 7/8" LAMI I.G. (3/16" T, 1/4" AIR SPACE, 3/16" HS, .080 PVB, 3/16" HS)	UPGRADE FTL-4311, 4312, 4315
G - 7/8" LAMI I.G. (3/16" T, 1/4" AIR SPACE, 3/16" A, .075 VANCEVA, 3/16" HS)	FTL-4527, 4528, 4529, 4530
H - 7/8" LAMI I.G. (3/16" T, 1/4" AIR SPACE, 3/16" HS, .075 VANCEVA, 3/16" HS)	UPGRADE FTL-4527, 4528, 4529, 4530

DESIGN PRESSURES
 ALUM. FRENCH DOOR & SIDE LITES, IMPACT
 F2000 NTS 3 = 12 8000-11 D

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1

PGT Industries
NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED


D. QUALITY ASSURANCE
 1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS
 1. Notice of Acceptance No. 09-0312.02 issued to D.I. DuPont DuPonts & Co., Inc. for their "DuPont Butacitec PVB Interlayer" dated 05/13/09, expiring on 12/11/10.
 2. Notice of Acceptance No. 06-0216.06 issued to Solvix Inc. for their "Saflex IIIIG Clear or colored interlayer" dated 05/04/06, expiring on 05/21/11.
 3. Notice of Acceptance No. 08-0528.08 issued to Solvix Inc. for their "Vanacea Composites Glass Interlayer" dated 7/17/05, expiring on 12/11/13.

F. STATEMENTS
 1. Statement letter of conformance, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 2. Statement letter of no financial interest, dated October 22, 2009, signed and sealed by Robert L. Clark, P.E.
 3. Laboratory compliance letter for Test Report No. FTL-4921, issued by Fenestration Testing Laboratory, Inc., dated June 26, 2006, signed and sealed by Edmundo Largaespada, P.E.
 4. Proposal No. 08-1891 issued by BCCO, dated January 26, 2009, signed by Ismael Chardas, P.E.

G. OTHER
 1. Notice of Acceptance No. 07-0103.02, issued to PGT Industries for their Series FD-250 Outswing Aluminum French Door w/Sidelites - L.M.L., approved on 03/15/07 and expiring on 02/24/10.

Manuel Perez, P.E.
 Product Control Registrar
 NOA No. 09-1828-19
 Expiration Date: February 24, 2015
 Approval Date: February 19, 2010
 Page 1



IN-SITE DESIGN GROUP INC
 1609 RODMAN STREET
 HOLLYWOOD, FLORIDA 33020
 AA26001758
 954 921 5333
 FAX 954 921 6769
 PROJECT COORDINATOR:
 ANNIE CARRUTHERS
 CGC 1511058
 ARCHITECT
 SAMUEL R. UCCELLO

STATE OF FLORIDA LICENSE No. AR-0015997

SEAL

PROJECT:
 SULLIVAN RESIDENCE

ADDRESS:
 1128 N. NORTHLAKE DR.
 HOLLYWOOD, FL 33019

DISTRIBUTION
 APRIL-16-2010
 HISTORIC BOARD
 SUBMITTAL
 PETITION NO: 10-C-17
 VARIANCE SUBMITTAL

JULY-12-2010
 PERMIT SUBMITTAL

REVISIONS

Date of Issue
 JULY-12-10

PRODUCT APPROVALS
A-11.1

27 #8021B 6063-T6 GEAR HINGE, JAMB
 28 #8020A 6063-T6 GEAR HINGE, COVER
 29 #8018 6063-T5 HINGE, BACK-UP
 30 #8019A 6063-T6 GEAR HINGE, DOOR
 37 #8039 6063-T6 TRUSS CLAMP
 61 #8028 6063-T5 SL HEAD TRIM
 64 #8056 6063-T4 SUBSILL, OPTIONAL
 70 #8010 6063-T6 NARROW SL JAMB
 80 #8033B 6105-T5 FD ASS'Y BEAM
 105 #8022 6063-T5 BACKBEAD
 106 #8026A 6063-T5 SL BACKBEAD
 107 #8023A 6063-T5 7/16" BEAD
 108 #8024A 6063-T5 I.G. BEAD
 62 #8029 6063-T5 SL JAMB TRIM

PRODUCT REVISED as complying with the Florida Building Code Acceptance No. 09-1028-10 Application Date 08/28/10 By: *Michael Perry* Miami Dade Product Control Division

Revised By: F.K.	Date: 10/12/08	Revision: B	DESCRIPTION: UPDATE ITEM 8
Revised By: J.R.	Date: 06/22/09	Revision: C	NEW PAGE
Revised By: J.R.	Date: 01/26/10	Revision: D	NO CHANGES THIS SHEET
Checked By: F.K.	Date: 12/23/04	L.T.	4/8/05

1670 TECHNOLOGY DRIVE
 NOKOMIS, FL 34275
 P.O. BOX 1629
 NOKOMIS, FL 34274

PGT
EXTRUSION PROFILES
ALUM. FRENCH DOOR & SIDE LITES, IMPACT
 Schedule: 1/2 Size: 9 x 12 Drawing No: 8000-11 Rev: D

Robert L. Clark, P.E.
PE #39712
Structural

DETAIL A (CONCRETE)
 (SINGLE PANEL)
 ANCHOR TYPES: 1 OR 2
DETAIL B (WOOD)
 (SINGLE PANEL)
 ANCHOR TYPES: 2 OR 3
DETAIL C (CONCRETE)
 (2 OR MORE PANELS)
 ANCHOR TYPES: 1 OR 2
DETAIL D (WOOD)
 (2 OR MORE PANELS)
 ANCHOR TYPES: 2 OR 3

ANCHORAGE SPACING REQUIREMENTS:
 1. DETAILS A AND B ABOVE REPRESENT ANCHORING OF SINGLE X DOORS, OR INDIVIDUAL SIDE LITE O PANELS WITH FULL OR NARROW WIDTH JAMBS. DETAILS C AND D ABOVE REPRESENT ANCHORING OF ANY MIXTURE OF DOUBLE XX DOORS, SINGLE X DOORS, NARROW JAMB OR FULL JAMB SIDE LITE PANELS, FOR MULTIPLE-PANEL INSTALLATIONS OF TWO OR MORE PANELS. UNLESS OTHERWISE STATED, DIMENSIONS OF DETAILS A THROUGH D ARE MAXIMUMS.
 2. ANCHOR TYPES: 1 - 1/4" ELCO ULTRACON 2 - 1/4" ELCO SS4 CRETE-FLEX 3 - #12 STEEL SCREW (G5)
 CONCRETE SUBSTRATE USE TYPE 1 AT 1 3/8" MIN. EMBEDMENT OR TYPE 2 AT 1 3/4" EMBEDMENT. 1 3/4" MIN. EDGE DISTANCE FOR BOTH. WOOD SUBSTRATE - USE TYPE 2 OR TYPE 3 AT 1 3/8" MIN. EMBEDMENT.
 3. SINGLE PANEL CONFIGURATIONS: (DETAIL A, CONCRETE SUBSTRATE. DETAIL B, WOOD SUBSTRATE)
 HEAD AND SILL.....6" MAX. FROM FRAME CORNERS.
 JAMBS.....11" MAX. FROM FRAME CORNERS, 18.500" MAX. O.C. CONCRETE SUBSTRATE (DETAIL A) AND 10.571" MAX. O.C. WOOD SUBSTRATE (DETAIL B).
 4. TWO OR MORE PANEL CONFIGURATIONS: (DETAIL C, CONCRETE SUBSTRATE)
 HEAD AND SILL.....6" MAX. FROM FRAME CORNERS, AND AT 3" AND 6" MAX. ON EACH SIDE OF ASSEMBLY BEAM AND/OR ASTRAGAL LOCATIONS (CLUSTER OF 4). JAMBS.....11" MAX. FROM FRAME CORNERS AND 18.500" MAX. O.C.
 5. TWO OR MORE PANEL CONFIGURATIONS: (DETAIL D, WOOD SUBSTRATE)
 HEAD AND SILL.....6" MAX. FROM FRAME CORNERS, AND AT 3", 6", 9" AND 12" MAX. ON EACH SIDE OF ASSEMBLY BEAM AND/OR ASTRAGAL LOCATIONS (CLUSTER OF 8). PLUS ENVICROLED ANCHORS OUTSIDE CLUSTERS, REQUIRED ONLY ON PANEL WIDTHS OVER 27 3/4". JAMBS.....11" MAX. FROM FRAME CORNERS AND 10.571" MAX. O.C.

REMOVE NOTE PERTAINING TO ANCHORAGE OUTSIDE MTD COUNTY. (SEE ANCHORAGE PER REGION AND REVISE NOTES 2, 3 & 6.)
 NO CHANGE THIS SHEET
 CHANGED "TAPCON" TO "ULTRACON".
 NO CHANGES THIS SHEET

PRODUCT REVISED as complying with the Florida Building Code Acceptance No. 09-1028-10 Application Date 08/28/10 By: *Michael Perry* Miami Dade Product Control Division

Revised By: F.K.	Date: 10/12/08	Revision: B	DESCRIPTION: REMOVE NOTE PERTAINING TO ANCHORAGE OUTSIDE MTD COUNTY. (SEE ANCHORAGE PER REGION AND REVISE NOTES 2, 3 & 6.)
Revised By: J.R.	Date: 06/22/09	Revision: C	NO CHANGE THIS SHEET
Revised By: J.R.	Date: 01/26/10	Revision: D	CHANGED "TAPCON" TO "ULTRACON".
Checked By: F.K.	Date: 12/23/04	L.T.	4/8/05

1670 TECHNOLOGY DRIVE
 NOKOMIS, FL 34275
 P.O. BOX 1629
 NOKOMIS, FL 34274

PGT
ANCHORAGE SPACING
ALUM. FRENCH DOOR & SIDE LITES, IMPACT
 Schedule: 1/4 Size: 10 x 12 Drawing No: 8000-11 Rev: D

Robert L. Clark, P.E.
PE #39712
Structural

TYPICAL SIDE LITE SILL (DIRECT TO CONCRETE)
OPTIONAL SIDE LITE SILL (SUBSILL TO CONCRETE)
TYPICAL SIDE LITE SILL (DIRECT TO WOOD)
OPTIONAL SIDE LITE SILL (SUBSILL TO WOOD)

TYPICAL DOOR & SIDE LITE HEAD

PRODUCT REVISED as complying with the Florida Building Code Acceptance No. 09-1028-10 Application Date 08/28/10 By: *Michael Perry* Miami Dade Product Control Division

Revised By: F.K.	Date: 10/12/08	Revision: B	DESCRIPTION: UPDATE ANCHORAGE AND NOTES
Revised By: J.R.	Date: 06/22/09	Revision: C	CHANGED MIN KSI OF CONCRETE. ADDED SIDE LITE SILL DETAIL. REORGANIZED DETAILS.
Revised By: J.R.	Date: 01/26/10	Revision: D	CHANGED "TAPCON" TO "ULTRACON".
Checked By: F.K.	Date: 12/23/04	L.T.	4/8/05

1670 TECHNOLOGY DRIVE
 NOKOMIS, FL 34275
 P.O. BOX 1629
 NOKOMIS, FL 34274

PGT
ANCHORAGE DETAILS
ALUM. FRENCH DOOR & SIDE LITES, IMPACT
 Schedule: 1/4 Size: 11 x 12 Drawing No: 8000-11 Rev: D

Robert L. Clark, P.E.
PE #39712
Structural

TYPICAL DOOR SILL (DIRECT TO CONCRETE)
OPTIONAL DOOR SILL (SUBSILL TO CONCRETE)
TYPICAL DOOR SILL (DIRECT TO WOOD)
OPTIONAL DOOR SILL (SUBSILL TO WOOD)

TYPICAL DOOR & SIDE LITE JAMB

REVIEWING IS ONLY FOR CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND TO ASSIST THE CONTRACTOR TO UNDERSTAND THE WORK. FULL RESPONSIBILITY FOR THE CORRECTNESS, ACCURACY AND COMPLETENESS OF THE SHOP DRAWINGS SHALL REMAIN WITH THE CONTRACTOR AND HE WILL BE RESPONSIBLE FOR THE WORK AND PERFORM IN ACCORDANCE WITH INFORMATION GIVEN IN THE ORIGINAL CONTRACT DOCUMENTS AND SPECIFICATIONS. CONTRACTOR SHALL BE RESPONSIBLE FOR DIMENSIONS TO BE CONFIRMED AND CORRELATED AT THE JOB SITE FOR INFORMATION THAT PERTAINS SOLELY TO THE FABRICATION PROCESS OR TO TECHNIQUES OF CONSTRUCTION AND FOR COORDINATION OF THE WORK OF ALL TRADES.


APPROVED
 NOV 1 2010
 CITY OF HOLLYWOOD, FLA. STRUCTURAL

Revised By: F.K.	Date: 10/12/08	Revision: B	DESCRIPTION: NEW SILL, ADD SUBSILL AND ALTERNATE TOP & BOTTOM RAIL EXTRUSIONS. CHANGED MIN KSI OF CONCRETE. ADDED LOW RISE SILL OPTION. REORGANIZED DETAILS.
Revised By: J.R.	Date: 06/22/09	Revision: C	NO CHANGES THIS SHEET
Revised By: J.R.	Date: 01/26/10	Revision: D	NO CHANGES THIS SHEET
Checked By: F.K.	Date: 12/23/04	L.T.	4/8/05

1670 TECHNOLOGY DRIVE
 NOKOMIS, FL 34275
 P.O. BOX 1629
 NOKOMIS, FL 34274

PGT
ANCHORAGE DETAILS
ALUM. FRENCH DOOR & SIDE LITES, IMPACT
 Schedule: 1/4 Size: 12 x 12 Drawing No: 8000-11 Rev: D

Robert L. Clark, P.E.
PE #39712
Structural



IN-SITE DESIGN GROUP INC
 1608 RODMAN STREET
 HOLLYWOOD, FLORIDA 33020
 AA26001758
 954 921 5333
 FAX 954 921 6769
 PROJECT COORDINATOR:
 ANNIE CARRUTHERS
 CGC 151068
 ARCHITECT
 SAMUEL R. UCCELLO

STATE OF FLORIDA LICENSE NO. AF-001997

THESE DESIGN AND DRAWINGS ARE THE COPYRIGHTED PROPERTY OF IN-SITE DESIGN GROUP, INC. AND MAY NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF THE COMPANY. THE CONTRACTOR MUST CHECK AND VERIFY ALL DIMENSIONS OF THE JOB AND BE RESPONSIBLE FOR SAME. REPORTING ANY DISCREPANCIES TO THE ARCHITECT BEFORE COMMENCEMENT OF WORK. DRAWINGS ARE NOT TO BE SCALED.

PROJECT:
 SULLIVAN RESIDENCE

ADDRESS:
 1128 N. NORTHLAKE DR.
 HOLLYWOOD, FL 33019

DISTRIBUTION
 APRIL-16-2010
 HISTORIC BOARD
 SUBMITTAL
 PETITION NO: 10-C-17
 VARIANCE SUBMITTAL

JULY-12-2010
 PERMIT SUBMITTAL

REVISIONS

Date of Issue
 JUL 17-10

PRODUCT APPROVALS

A-11.3

NOTICE OF ACCEPTANCE (NOA)

PGT Industries
1079 Technology Drive
Valdosta, GA 31674

Scope:
This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).
This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (in Miami-Dade County) and/or the AHJ (in areas other than Miami-Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will bear the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series C-740 Outswing Aluminum Casement Window -L.M.L.
APPROVAL DOCUMENT: Drawing No. 7045-8, titled "Aluminum Casement Window, Impact", sheets 1 through 13 of 13, dated 12/17/02 with revision "D" dated 06/23/05, prepared by manufacturer, signed and sealed by Lucas A. Turner, P.E., bearing the Miami-Dade County Product Control Approval stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: Large Missile Impact Resistant
LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL: If this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.
TERMINATION: This NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any condition of this NOA shall be cause for termination and removal of NOA.
ADVERTISING: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributor and shall be available for inspection at the job site at the request of the Building Official. This NOA renews NOA # 05-1128-11 and consists of this page 1 and evidence pages 1-1 and E-2, as well as approval document mentioned above.
The submitted documentation was reviewed by Manuel Perez, P.E.

NOA No. 08-0117-11
Expiration Date: May 22, 2013
Approval Date: May 15, 2008
Page 1

NOTICE OF ACCEPTANCE - EVIDENCE SUBMITTED

A. DRAWINGS

- Manufacturer's die drawings and sections.
- Drawing No. 7045-8, titled "Aluminum Casement Window, Impact", sheets 1 through 13 of 13, dated 12/17/02 with revision "D" dated 06/23/05, prepared by manufacturer, signed and sealed by Lucas A. Turner, P.E.

B. TESTS

- Test reports on:
 - Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - Large Missile Impact Test per FBC, TAS 201-94
 - Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of two outswing aluminum casement windows, prepared by Fenestration Testing Laboratory, Test Report No. FTL 4608 dated 05/10/05, signed and sealed by Edmundo Largaspada, P.E. (Submitted under NOA# 05-1128-11)
- Test reports on:
 - Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - Water Resistance Test, per FBC, TAS 202-94
 - Large Missile Impact Test per FBC, TAS 201-94
 - Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94
 along with marked-up drawings and installation diagram of two outswing aluminum casement windows, prepared by Fenestration Testing Laboratory, Test Report No. FTL 4607 dated 05/10/05, signed and sealed by Edmundo Largaspada, P.E. (Submitted under NOA# 05-1128-11)

- Test reports on:
 - Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - Large Missile Impact Test per FBC, TAS 201-94
 - Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of two outswing aluminum casement windows, prepared by Fenestration Testing Laboratory, Test Report No. FTL 3739 dated 12/28/03, signed and sealed by Joseph Chan, P.E. (Submitted under NOA# 03-0611-02)
- Test reports on:
 - Air Infiltration Test, per FBC, TAS 202-94
 - Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - Water Resistance Test, per FBC, TAS 202-94
 - Large Missile Impact Test per FBC, TAS 201-94
 - Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94
 along with marked-up drawings and installation diagram of two outswing aluminum casement windows, prepared by Fenestration Testing Laboratory, Test Report No. FTL 3587 dated 10/3/02, signed and sealed by Joseph Chan, P.E. (Submitted under NOA# 03-0611-02)

- C. CALCULATIONS**
 - Revised Anchor Calculations and structural analysis, prepared by manufacturer, dated 11/21/05, signed and sealed by Lucas A. Turner, P.E. Complies with ASTM E 1308-98
- D. QUALITY ASSURANCE**
 - Miami Dade Building Code Compliance Office (BCCO)

- E. MATERIAL CERTIFICATIONS**
 - Notice of Acceptance No. 05-1208-02 issued to E.I. DuPont DeNemours & Co., Inc. for their DuPont Brattice PVB Interlayer dated 01/05/06, expiring on 12/11/10.
 - Notice of Acceptance No. 06-0216-06 issued to Solutia Inc. for their Solutia HIG Clear or colored Interlayer dated 05/04/06, expiring on 05/21/11.

- F. STATEMENTS**
 - Statement letter of conformance, dated 12/19/02, signed and sealed by Robert L. Clark, P.E.
 - Statement letter of no financial interest, dated 12/19/02, signed and sealed by Robert L. Clark, P.E.
- G. OTHER**
 - Notice of Acceptance No. 05-1128-11, issued to PGT Industries for their Series C-740 Aluminum Casement Window -L.M.L., approved on 02/23/08, expiring on 05/22/08.

NOTICE OF ACCEPTANCE - EVIDENCE SUBMITTED

5. Test reports on:

- Air Infiltration Test, per FBC, TAS 202-94
- Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
- Water Resistance Test, per FBC, TAS 202-94
- Large Missile Impact Test per FBC, TAS 201-94
- Cyclic Wind Pressure Loading per FBC, TAS 203-94
- Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94

along with marked-up drawings and installation diagram of one outswing aluminum casement window, prepared by Fenestration Testing Laboratory, Test Report No. FTL 3582 dated 10/3/02, signed and sealed by Joseph Chan, P.E. (Submitted under NOA# 03-0611-02)

- Test reports on:
 - Air Infiltration Test, per FBC, TAS 202-94
 - Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - Water Resistance Test, per FBC, TAS 202-94
 - Large Missile Impact Test per FBC, TAS 201-94
 - Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94
 along with marked-up drawings and installation diagram of three aluminum outswing casement windows, prepared by Fenestration Testing Laboratory, Test Report No. FTL 3580 dated 10/3/02, signed and sealed by Joseph Chan, P.E. (Submitted under NOA# 03-0611-02)

- C. CALCULATIONS**
 - Revised Anchor Calculations and structural analysis, prepared by manufacturer, dated 11/21/05, signed and sealed by Lucas A. Turner, P.E. Complies with ASTM E 1308-98
- D. QUALITY ASSURANCE**
 - Miami Dade Building Code Compliance Office (BCCO)

- E. MATERIAL CERTIFICATIONS**
 - Notice of Acceptance No. 05-1208-02 issued to E.I. DuPont DeNemours & Co., Inc. for their DuPont Brattice PVB Interlayer dated 01/05/06, expiring on 12/11/10.
 - Notice of Acceptance No. 06-0216-06 issued to Solutia Inc. for their Solutia HIG Clear or colored Interlayer dated 05/04/06, expiring on 05/21/11.


- F. STATEMENTS**
 - Statement letter of conformance, dated 12/19/02, signed and sealed by Robert L. Clark, P.E.
 - Statement letter of no financial interest, dated 12/19/02, signed and sealed by Robert L. Clark, P.E.
- G. OTHER**
 - Notice of Acceptance No. 05-1128-11, issued to PGT Industries for their Series C-740 Aluminum Casement Window -L.M.L., approved on 02/23/08, expiring on 05/22/08.

NOTES - LARGE MISSILE WINDOWS

- GLAZING OPTIONS:
 - 5/16" LAMINATED GLASS COMPRISED OF (1) LITE OF 1/8" ANNEALED GLASS AND (1) LITE OF 1/8" HEAT STRENGTHENED GLASS W/ AN .090 INTERLAYER OF SOLUTIA OR DUPONT PVB.
 - 5/16" LAMINATED GLASS COMPRISED OF (2) LITES OF 1/8" HEAT STRENGTHENED GLASS W/ AN .090 INTERLAYER OF SOLUTIA OR DUPONT PVB.
 - 7/16" LAMINATED GLASS COMPRISED OF (1) LITE OF 3/16" ANNEALED GLASS AND (1) LITE OF 3/16" HEAT STRENGTHENED GLASS W/ AN .090 INTERLAYER OF SOLUTIA OR DUPONT PVB.
 - 7/16" LAMINATED GLASS COMPRISED OF (2) LITES OF 3/16" HEAT STRENGTHENED GLASS W/ AN .090 INTERLAYER OF SOLUTIA OR DUPONT PVB.
- CONFIGURATIONS OPTIONS:

UNEQUAL LITES	UNEQUAL LITES	UNEQUAL LITES
UNEQUAL LITES	UNEQUAL LITES	UNEQUAL LITES
- NOA DRAWING TABLE OF CONTENTS SHEET

NOTES	1
GLAZING DETAILS	2-4
ELEVATIONS	5-9
DESIGN PRESSURE TABLES	10
SECTIONS	11
CORNER CONSTRUCTION	11-12
EXTRUSION PROFILES	12
PARTS LIST	1,3,4,13
ANCHORAGE	



NOA DRAWING TABLE OF CONTENTS SHEET

NOTES	1
GLAZING DETAILS	2-4
ELEVATIONS	5-9
DESIGN PRESSURE TABLES	10
SECTIONS	11
CORNER CONSTRUCTION	11-12
EXTRUSION PROFILES	12
PARTS LIST	1,3,4,13
ANCHORAGE	

- CONFIGURATIONS: X, XX, XO, OX, XXO, OXX AND O
- DESIGN PRESSURE PATTERNS/COMPARATIVE ANALYSIS TABLES:
 - NEGATIVE DESIGN LOADS BASED ON TESTED TEST PRESSURE AND GLASS TABLES ASTM E 1300-98.
 - POSITIVE DESIGN LOADS BASED ON WATER TEST PRESSURE AND GLASS TABLES ASTM E 1300-98.
 - DESIGN PRESSURES UNDER 40 P.S.F. NOT APPLICABLE IN MIAMI-DADE COUNTY.
 - FOR "X" CONFIGURATIONS SEE SHEET 5.
 - FOR "XX" CONFIGURATIONS SEE SHEET 6.
 - FOR "XO" & "OX" CONFIGURATIONS SEE SHEET 7.
 - FOR "XXO" & "OXX" CONFIGURATIONS SEE SHEET 8.
 - FOR UNEQUAL LITE "XOX" "XOX" & "XOX" CONFIGURATIONS SEE SHEET 9.
- ANCHORAGE: THE 33% STRESS INCREASE HAS NOT BEEN USED IN THE DESIGN OF THIS PRODUCT. SEE SHEETS 3, 4 AND 13 FOR ADDITIONAL ANCHORAGE INFORMATION.

- HEAD & SILL:**
MAX. 4" FROM CORNERS
MAX. 4" & 7" ON EACH SIDE OF MEETING RAILS
MAX. 14 1/2" SPACING ON VENTS
MAX. 13" SPACING ON FIXED LITES
(2) ANCHORS 3" APART AT MID-SPAN ON FIXED LITE ONLY
- JAMBS:**
MAX. 4" FROM CORNERS
MAX. 13" SPACING
(2) ANCHORS 3" APART AT MID-SPAN
- SEE SHEET 10 FOR APPROVED ANCHORS. 1M" TAPCONS OR 1/4" SS4 CRETE-FLEX MAY BE USED IN CONCRETE OR WOOD APPLICATIONS TO ACHIEVE THE DESIGN PRESSURES SHOWN IN SHEETS 5 THROUGH 9. SEE SHEETS 5 THROUGH 9 FOR DESIGN PRESSURE LIMITATIONS WHEN ANCHORING WITH #12 SCREWS.
- SHUTTER REQUIREMENT: NONE REQUIRED
- NARROW JOINT SEALANT IS USED ON ALL FOUR CORNERS OF THE FRAME.
- REFERENCE TEST REPORTS: FTL-3580, FTL-3582, FTL-3729, FTL-4607 AND FTL-4608

Notes	1	ADD 1/8" L.G. & MOVE GLAZING DETAILS TO SHEET 2	1075 REGULAR CURTAIN DRAPES
Notes	2	NO CHANGE THIS SHEET	ADJUSTABLE CURTAIN DRAPES
Notes	3	ADD 20" HT. GLASS TYPES F & G. REUSE ANCHORAGE	P.P. NOT USED
Notes	4		ANCHORING TABLE




NOTES AND TABLE OF CONTENTS

DATE	DATE	DATE	DATE
12/17/02	06/23/05	02/23/08	05/22/08

PRODUCT REVIEWED
as required by the Florida Building Code
Florida Building Code, Chapter 6
Approved: 05-01-11
Expire Date: 05-22-08
Manuel Perez, P.E.
Miami-Dade County Product Control Division

PRODUCT REVIEWED
as required by the Florida Building Code
Florida Building Code, Chapter 6
Approved: 05-01-11
Expire Date: 05-22-08
Manuel Perez, P.E.
Miami-Dade County Product Control Division



IN-SITE DESIGN GROUP INC

1609 RODMAN STREET
HOLLYWOOD, FLORIDA 33020
AA26001758
954 921 5333
FAX 954 921 6769
PROJECT COORDINATOR:
ANNIE CARRUTHERS
COC 1511058
ARCHITECT
SAMUEL R. UCCELLO

SEAL
STATE OF FLORIDA LICENSE NO. AR-001997

THESE DESIGNS AND DRAWINGS ARE THE COPYRIGHTED PROPERTY OF IN-SITE DESIGN GROUP, INC. AND MAY NOT BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF IN-SITE DESIGN GROUP, INC. THE CONTRACTOR MUST CHECK AND VERIFY ALL DIMENSIONS OF THE JOB AND BE RESPONSIBLE FOR SAFE REPORTING ANY DISCREPANCIES TO THE ARCHITECT BEFORE COMMENCEMENT OF WORK. DRAWINGS ARE NOT TO BE SCALED.


PROJECT:
SULLIVAN RESIDENCE

ADDRESS:
1128 N. NORTHLAKE DR.
HOLLYWOOD, FL 33019

DISTRIBUTION
APRIL-16-2010
HISTORIC BOARD
SUBMITTAL
PETITION NO: 10-C-17
VARIANCE SUBMITTAL

JULY-12-2010
PERMIT SUBMITTAL

REVISIONS




- REVIEWED
- NOT APPROVED
- REVIEWED AS NOTED
- REVISE & RESUBMIT

REVIEWING IS ONLY FOR CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND TO ASSIST THE CONTRACTOR TO EXPEDITE HIS WORK. FULL RESPONSIBILITY FOR THE CORRECTNESS, ADEQUACY AND ACCURACY OF THE SHOP DRAWINGS SHALL REMAIN WITH THE CONTRACTOR AND HE WILL BE EXPECTED TO COMPLY AND PERFORM IN ACCORDANCE WITH INFORMATION GIVEN IN THE ORIGINAL CONTRACT DOCUMENTS, OR AS AMENDED IN WRITING. CONTRACTOR SHALL BE RESPONSIBLE FOR DIMENSIONS TO BE CONFIRMED AND CORRELATED AT THE JOB SITE FOR INFORMATION THAT PERTAINS SOLELY TO THE FABRICATION PROCESS OR TO TECHNIQUES OF CONSTRUCTION AND FOR COORDINATION OF THE WORK OF ALL TRADES.


BY: SLU
IN-SITE DESIGN GROUP, INC.
DATE: 7.9.10

PRODUCT APPROVALS

A-11.4



ITEM	DWG #	DESCRIPTION
1	7015	MAXIM SINK-E LOCK
2	7015	SINK-E LOCK KEYS
3	7015	FRAME CORNER KEY
4	7015A	FRAMING ANGLE
5	7015A	FRAMING ANGLE
6	7015A	FRAMING ANGLE
7	7015A	FRAMING ANGLE
8	7015A	FRAMING ANGLE
9	7015A	FRAMING ANGLE
10	7015A	FRAMING ANGLE
11	7015A	FRAMING ANGLE
12	7015A	FRAMING ANGLE
13	7015A	FRAMING ANGLE
14	7015A	FRAMING ANGLE
15	7015A	FRAMING ANGLE
16	7015A	FRAMING ANGLE
17	7015A	FRAMING ANGLE
18	7015A	FRAMING ANGLE
19	7015A	FRAMING ANGLE
20	7015A	FRAMING ANGLE
21	7015A	FRAMING ANGLE
22	7015A	FRAMING ANGLE
23	7015A	FRAMING ANGLE
24	7015A	FRAMING ANGLE
25	7015A	FRAMING ANGLE
26	7015A	FRAMING ANGLE
27	7015A	FRAMING ANGLE
28	7015A	FRAMING ANGLE
29	7015A	FRAMING ANGLE
30	7015A	FRAMING ANGLE
31	7015A	FRAMING ANGLE
32	7015A	FRAMING ANGLE
33	7015A	FRAMING ANGLE
34	7015A	FRAMING ANGLE
35	7015A	FRAMING ANGLE
36	7015A	FRAMING ANGLE
37	7015A	FRAMING ANGLE
38	7015A	FRAMING ANGLE
39	7015A	FRAMING ANGLE
40	7015A	FRAMING ANGLE
41	7015A	FRAMING ANGLE
42	7015A	FRAMING ANGLE
43	7015A	FRAMING ANGLE
44	7015A	FRAMING ANGLE
45	7015A	FRAMING ANGLE
46	7015A	FRAMING ANGLE
47	7015A	FRAMING ANGLE
48	7015A	FRAMING ANGLE
49	7015A	FRAMING ANGLE
50	7015A	FRAMING ANGLE
51	7015A	FRAMING ANGLE
52	7015A	FRAMING ANGLE
53	7015A	FRAMING ANGLE
54	7015A	FRAMING ANGLE
55	7015A	FRAMING ANGLE
56	7015A	FRAMING ANGLE
57	7015A	FRAMING ANGLE
58	7015A	FRAMING ANGLE
59	7015A	FRAMING ANGLE
60	7015A	FRAMING ANGLE
61	7015A	FRAMING ANGLE
62	7015A	FRAMING ANGLE
63	7015A	FRAMING ANGLE
64	7015A	FRAMING ANGLE
65	7015A	FRAMING ANGLE
66	7015A	FRAMING ANGLE
67	7015A	FRAMING ANGLE
68	7015A	FRAMING ANGLE
69	7015A	FRAMING ANGLE
70	7015A	FRAMING ANGLE
71	7015A	FRAMING ANGLE
72	7015A	FRAMING ANGLE
73	7015A	FRAMING ANGLE
74	7015A	FRAMING ANGLE
75	7015A	FRAMING ANGLE
76	7015A	FRAMING ANGLE
77	7015A	FRAMING ANGLE
78	7015A	FRAMING ANGLE
79	7015A	FRAMING ANGLE
80	7015A	FRAMING ANGLE
81	7015A	FRAMING ANGLE
82	7015A	FRAMING ANGLE
83	7015A	FRAMING ANGLE
84	7015A	FRAMING ANGLE
85	7015A	FRAMING ANGLE
86	7015A	FRAMING ANGLE
87	7015A	FRAMING ANGLE
88	7015A	FRAMING ANGLE
89	7015A	FRAMING ANGLE
90	7015A	FRAMING ANGLE
91	7015A	FRAMING ANGLE
92	7015A	FRAMING ANGLE
93	7015A	FRAMING ANGLE
94	7015A	FRAMING ANGLE
95	7015A	FRAMING ANGLE
96	7015A	FRAMING ANGLE
97	7015A	FRAMING ANGLE
98	7015A	FRAMING ANGLE
99	7015A	FRAMING ANGLE
100	7015A	FRAMING ANGLE



ITEM	DWG #	DESCRIPTION
1	7015	MAXIM SINK-E LOCK
2	7015	SINK-E LOCK KEYS
3	7015	FRAME CORNER KEY
4	7015A	FRAMING ANGLE
5	7015A	FRAMING ANGLE
6	7015A	FRAMING ANGLE
7	7015A	FRAMING ANGLE
8	7015A	FRAMING ANGLE
9	7015A	FRAMING ANGLE
10	7015A	FRAMING ANGLE
11	7015A	FRAMING ANGLE
12	7015A	FRAMING ANGLE
13	7015A	FRAMING ANGLE
14	7015A	FRAMING ANGLE
15	7015A	FRAMING ANGLE
16	7015A	FRAMING ANGLE
17	7015A	FRAMING ANGLE
18	7015A	FRAMING ANGLE
19	7015A	FRAMING ANGLE
20	7015A	FRAMING ANGLE
21	7015A	FRAMING ANGLE
22	7015A	FRAMING ANGLE
23	7015A	FRAMING ANGLE
24	7015A	FRAMING ANGLE
25	7015A	FRAMING ANGLE
26	7015A	FRAMING ANGLE
27	7015A	FRAMING ANGLE
28	7015A	FRAMING ANGLE
29	7015A	FRAMING ANGLE
30	7015A	FRAMING ANGLE
31	7015A	FRAMING ANGLE
32	7015A	FRAMING ANGLE
33	7015A	FRAMING ANGLE
34	7015A	FRAMING ANGLE
35	7015A	FRAMING ANGLE
36	7015A	FRAMING ANGLE
37	7015A	FRAMING ANGLE
38	7015A	FRAMING ANGLE
39	7015A	FRAMING ANGLE
40	7015A	FRAMING ANGLE
41	7015A	FRAMING ANGLE
42	7015A	FRAMING ANGLE
43	7015A	FRAMING ANGLE
44	7015A	FRAMING ANGLE
45	7015A	FRAMING ANGLE
46	7015A	FRAMING ANGLE
47	7015A	FRAMING ANGLE
48	7015A	FRAMING ANGLE
49	7015A	FRAMING ANGLE
50	7015A	FRAMING ANGLE
51	7015A	FRAMING ANGLE
52	7015A	FRAMING ANGLE
53	7015A	FRAMING ANGLE
54	7015A	FRAMING ANGLE
55	7015A	FRAMING ANGLE
56	7015A	FRAMING ANGLE
57	7015A	FRAMING ANGLE
58	7015A	FRAMING ANGLE
59	7015A	FRAMING ANGLE
60	7015A	FRAMING ANGLE
61	7015A	FRAMING ANGLE
62	7015A	FRAMING ANGLE
63	7015A	FRAMING ANGLE
64	7015A	FRAMING ANGLE
65	7015A	FRAMING ANGLE
66	7015A	FRAMING ANGLE
67	7015A	FRAMING ANGLE
68	7015A	FRAMING ANGLE
69	7015A	FRAMING ANGLE
70	7015A	FRAMING ANGLE
71	7015A	FRAMING ANGLE
72	7015A	FRAMING ANGLE
73	7015A	FRAMING ANGLE
74	7015A	FRAMING ANGLE
75	7015A	FRAMING ANGLE
76	7015A	FRAMING ANGLE
77	7015A	FRAMING ANGLE
78	7015A	FRAMING ANGLE
79	7015A	FRAMING ANGLE
80	7015A	FRAMING ANGLE
81	7015A	FRAMING ANGLE
82	7015A	FRAMING ANGLE
83	7015A	FRAMING ANGLE
84	7015A	FRAMING ANGLE
85	7015A	FRAMING ANGLE
86	7015A	FRAMING ANGLE
87	7015A	FRAMING ANGLE
88	7015A	FRAMING ANGLE
89	7015A	FRAMING ANGLE
90	7015A	FRAMING ANGLE
91	7015A	FRAMING ANGLE
92	7015A	FRAMING ANGLE
93	7015A	FRAMING ANGLE
94	7015A	FRAMING ANGLE
95	7015A	FRAMING ANGLE
96	7015A	FRAMING ANGLE
97	7015A	FRAMING ANGLE
98	7015A	FRAMING ANGLE
99	7015A	FRAMING ANGLE
100	7015A	FRAMING ANGLE

APPROVED
NOV 5 2010
CITY OF HOLLYWOOD, FLA.
STRUCTURAL

REVIEWED: NOT APPROVED:
 REVIEWED AS NOTED: REVISE & RESUBMIT:

REVIEWING IS ONLY FOR CONFORMANCE WITH THE DESIGN CONCEPT OF THE PROJECT AND TO ASSIST THE CONTRACTOR TO EXPEDITE HIS WORK. FULL RESPONSIBILITY FOR THE CORRECTNESS, ADEQUACY AND ACCURACY OF THE SHOP DRAWINGS SHALL REMAIN WITH THE CONTRACTOR AND HE WILL BE EXPECTED TO COMPLY AND PERFORM IN ACCORDANCE WITH INFORMATION GIVEN IN THE ORIGINAL CONTRACT DOCUMENTS, OR AS AMENDED IN WRITING. CONTRACTOR SHALL BE RESPONSIBLE FOR DIMENSIONS TO BE CONFIRMED AND CORRELATED AT THE JOB SITE FOR INFORMATION THAT PERTAINS SOLELY TO THE FABRICATION PROCESS OR TO TECHNIQUES OR CONSTRUCTION AND FOR COORDINATION OF THE WORK OF ALL TRADES.

BY: S&U
IN-SITE DESIGN GROUP, INC.
DATE: 7-9-10

PROJECT:
SULLIVAN RESIDENCE

ADDRESS:
1128 N. NORTHLAKE DR.
HOLLYWOOD, FL 33019

DISTRIBUTION
APRIL -16-2010
HISTORIC BOARD
SUBMITTAL
PETITION NO: 10-C-17
VARIANCE SUBMITTAL

JULY-12-2010
PERMIT SUBMITTAL


REVISIONS

IN-SITE DESIGN GROUP INC
1609 RODMAN STREET
HOLLYWOOD, FLORIDA 33020
AA26001758
954 921 5333
FAX 954 921 6769
PROJECT COORDINATOR:
ANNIE CARRUTHERS
CGC 1511058
ARCHITECT
SAMUEL R. UCCELLO

STATE OF FLORIDA LICENSE: No AR-0019997

DATE OF ISSUE
JULY 12-10

PRODUCT APPROVALS
A-11.6



IN-SITE DESIGN GROUP INC

16009 RODMAN STREET
HOLLYWOOD, FLORIDA 33020
AA26001758
954 921 5333
FAX 954 921 6769
PROJECT COORDINATOR:
ANNIE CARRUTHERS
CCG 1511058
ARCHITECT
SAMUEL R. UCCELLO

SEAL
STATE OF FLORIDA LICENSE NO. AR-0015997

THESE DESIGNS AND DRAWINGS ARE THE
REGISTERED PROPERTY OF IN-SITE DESIGN
GROUP, INC. AND MAY NOT BE REPRODUCED
OR TRANSMITTED IN ANY FORM OR BY ANY
MEANS, ELECTRONIC OR MECHANICAL,
INCLUDING PHOTOCOPYING, RECORDING,
OR BY ANY INFORMATION STORAGE AND
RETRIEVAL SYSTEM, WITHOUT THE WRITTEN
CONSENT OF THE COMPANY. THE CONTRACTOR MUST CHECK
AND VERIFY ALL DIMENSIONS OF THE JOB AND
BE RESPONSIBLE FOR ANY DISCREPANCIES
DISCOVERED TO THE ARCHITECT BEFORE
COMPLETION OF WORK. DRAWINGS ARE NOT
TO BE SCALED.

PROJECT:
SULLIVAN RESIDENCE

ADDRESS:
1128 N. NORTHLAKE DR.
HOLLYWOOD, FL 33019

DISTRIBUTION
APRIL-16-2010
HISTORIC BOARD
SUBMITTAL
PETITION NO: 10-C-17
VARIANCE SUBMITTAL

JULY-12-2010
PERMIT SUBMITTAL

REVISIONS

Date of Issue
JULY 12-10

PRODUCT
APPROVALS

A-11.7




TABLE 1. DESIGN PRESSURES, FLANGED WINDOW DIMENSIONS ARE TYPICAL


GLASS TYPE:	A. 7/16\"/>		B. 7/16\"/>		C. 1 1/16\"/>		D. 1 1/16\"/>	
	WINDOW TYPE	WINDOW DIMENSION	WINDOW TYPE	WINDOW DIMENSION	WINDOW TYPE	WINDOW DIMENSION	WINDOW TYPE	WINDOW DIMENSION
48,000 AREA	A/B/C/D	28,500	34,000	38,500	43,000	48,000	48,000	48,000
54,500 AREA	A/B/C/D	9,700 SQ FT	11,900 SQ FT	13,440 SQ FT	15,300 SQ FT	15,800 SQ FT	16,300 SQ FT	16,300 SQ FT
60,000 AREA	A/B/C/D	10,700 SQ FT	12,800 SQ FT	14,560 SQ FT	17,000 SQ FT	17,600 SQ FT	18,100 SQ FT	18,100 SQ FT
65,500 AREA	A/B/C/D	11,800 SQ FT	14,100 SQ FT	16,000 SQ FT	18,000 SQ FT	18,800 SQ FT	19,600 SQ FT	20,000 SQ FT
71,000 AREA	A/B/C/D	12,800 SQ FT	15,400 SQ FT	17,300 SQ FT	19,200 SQ FT	20,000 SQ FT	21,000 SQ FT	21,800 SQ FT
76,500 AREA	A/B/C/D	14,000 SQ FT	16,800 SQ FT	18,800 SQ FT	20,800 SQ FT	21,800 SQ FT	22,800 SQ FT	23,500 SQ FT
82,000 AREA	A/B/C/D	15,200 SQ FT	18,300 SQ FT	20,600 SQ FT	22,800 SQ FT	23,800 SQ FT	24,800 SQ FT	25,500 SQ FT
87,500 AREA	A/B/C/D	16,500 SQ FT	19,900 SQ FT	22,600 SQ FT	25,000 SQ FT	26,000 SQ FT	27,000 SQ FT	27,500 SQ FT
93,000 AREA	A/B/C/D	17,800 SQ FT	21,600 SQ FT	24,600 SQ FT	27,400 SQ FT	28,400 SQ FT	29,400 SQ FT	30,000 SQ FT
98,500 AREA	A/B/C/D	19,200 SQ FT	23,400 SQ FT	26,800 SQ FT	30,000 SQ FT	31,000 SQ FT	32,000 SQ FT	32,000 SQ FT

NOTES: LARGE MISSILE WINDOWS
1. GLAZING OPTIONS:
A. 7/16\"/>


TABLE 2. DESIGN PRESSURES, FLANGED WINDOW DIMENSIONS ARE TYPICAL


GLASS TYPE:	A. 7/16\"/>		B. 7/16\"/>		C. 1 1/16\"/>		D. 1 1/16\"/>	
	WINDOW TYPE	WINDOW DIMENSION	WINDOW TYPE	WINDOW DIMENSION	WINDOW TYPE	WINDOW DIMENSION	WINDOW TYPE	WINDOW DIMENSION
48,000 AREA	A/B/C/D	28,500	34,000	38,500	43,000	48,000	48,000	48,000
54,500 AREA	A/B/C/D	9,700 SQ FT	11,900 SQ FT	13,440 SQ FT	15,300 SQ FT	15,800 SQ FT	16,300 SQ FT	16,300 SQ FT
60,000 AREA	A/B/C/D	10,700 SQ FT	12,800 SQ FT	14,560 SQ FT	17,000 SQ FT	17,600 SQ FT	18,100 SQ FT	18,100 SQ FT
65,500 AREA	A/B/C/D	11,800 SQ FT	14,100 SQ FT	16,000 SQ FT	18,000 SQ FT	18,800 SQ FT	19,600 SQ FT	20,000 SQ FT
71,000 AREA	A/B/C/D	12,800 SQ FT	15,400 SQ FT	17,300 SQ FT	19,200 SQ FT	20,000 SQ FT	21,000 SQ FT	21,800 SQ FT
76,500 AREA	A/B/C/D	14,000 SQ FT	16,800 SQ FT	18,800 SQ FT	20,800 SQ FT	21,800 SQ FT	22,800 SQ FT	23,500 SQ FT
82,000 AREA	A/B/C/D	15,200 SQ FT	18,300 SQ FT	20,600 SQ FT	22,800 SQ FT	23,800 SQ FT	24,800 SQ FT	25,500 SQ FT
87,500 AREA	A/B/C/D	16,500 SQ FT	19,900 SQ FT	22,600 SQ FT	25,000 SQ FT	26,000 SQ FT	27,000 SQ FT	27,500 SQ FT
93,000 AREA	A/B/C/D	17,800 SQ FT	21,600 SQ FT	24,600 SQ FT	27,400 SQ FT	28,400 SQ FT	29,400 SQ FT	30,000 SQ FT
98,500 AREA	A/B/C/D	19,200 SQ FT	23,400 SQ FT	26,800 SQ FT	30,000 SQ FT	31,000 SQ FT	32,000 SQ FT	32,000 SQ FT

PGT Industries
NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED
A. DRAWINGS (transferred from file # 07-0418.06)
1. Manufacturer's die drawings and sections.
2. Drawing No. 4259-4, titled "Aluminum Picture Window, Impact", sheets 1 through 12 of 12, prepared by manufacturer, dated 07/14/03 and last revised revision "B" on dated 4/4/07, signed and sealed by Robert L. Clark, P.E.



MIAMI-DADE COUNTY
BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION
NOTICE OF ACCEPTANCE (NOA)
PGT Industries
1878 Technology Drive,
Nokomis, FL 34275
SCOPE:
This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).





IN-SITE DESIGN GROUP INC

1609 RODMAN STREET
HOLLYWOOD, FLORIDA 33020
AA26001758
954 921 5333
PROJECT COORDINATOR:
ANNIE CARRUTHERS
CGC 1511058
ARCHITECT
SAMUEL R. UCCELLO

SEAL
STATE OF FLORIDA LICENSE No AR-0015987

THESE DESIGNS AND DRAWINGS ARE THE COPYRIGHTED PROPERTY OF IN-SITE DESIGN GROUP, INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF THE COPYRIGHT OWNER. THE CONTRACTOR MUST CHECK AND VERIFY ALL DIMENSIONS OF THE JOB AND BE RESPONSIBLE FOR SAFE REPORTING ANY DISCREPANCIES TO THE ARCHITECT BEFORE COMMENCEMENT OF WORK. DRAWINGS ARE NOT TO BE SCALED.

PROJECT:
SULLIVAN RESIDENCE

ADDRESS:
1128 N. NORTHLAKE DR.
HOLLYWOOD, FL 33019

DISTRIBUTION
APRIL-16-2010
HISTORIC BOARD
SUBMITTAL
PETITION NO: 10-C-17
VARIANCE SUBMITTAL

JULY-12-2010
PERMIT SUBMITTAL

REVISIONS

Date Of Issue
JULY 12-10

PRODUCT APPROVALS

A-11.8

EXTERIOR WINDOW MIAMI-DADE COUNTY PRODUCT APPROVALS AND NOA - FIXED WINDOW CONTINUED




TABLE 3. ANCHOR ON-CENTER DIMENSION BY ANCHOR TYPE - WOOD SUBSTRATE

ANCHOR TYPE	WINDOW "Y" DIMENSION											
	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	38"
1" DIA. STEEL SCREW (S)	10	12	14	16	18	20	22	24	26	28	30	32
2" DIA. STEEL SCREW (S)	12	14	16	18	20	22	24	26	28	30	32	34
3" DIA. STEEL SCREW (S)	14	16	18	20	22	24	26	28	30	32	34	36
4" DIA. STEEL SCREW (S)	16	18	20	22	24	26	28	30	32	34	36	38
5" DIA. STEEL SCREW (S)	18	20	22	24	26	28	30	32	34	36	38	40
6" DIA. STEEL SCREW (S)	20	22	24	26	28	30	32	34	36	38	40	42
7" DIA. STEEL SCREW (S)	22	24	26	28	30	32	34	36	38	40	42	44
8" DIA. STEEL SCREW (S)	24	26	28	30	32	34	36	38	40	42	44	46
9" DIA. STEEL SCREW (S)	26	28	30	32	34	36	38	40	42	44	46	48
10" DIA. STEEL SCREW (S)	28	30	32	34	36	38	40	42	44	46	48	50
11" DIA. STEEL SCREW (S)	30	32	34	36	38	40	42	44	46	48	50	52
12" DIA. STEEL SCREW (S)	32	34	36	38	40	42	44	46	48	50	52	54
13" DIA. STEEL SCREW (S)	34	36	38	40	42	44	46	48	50	52	54	56
14" DIA. STEEL SCREW (S)	36	38	40	42	44	46	48	50	52	54	56	58
15" DIA. STEEL SCREW (S)	38	40	42	44	46	48	50	52	54	56	58	60
16" DIA. STEEL SCREW (S)	40	42	44	46	48	50	52	54	56	58	60	62
17" DIA. STEEL SCREW (S)	42	44	46	48	50	52	54	56	58	60	62	64
18" DIA. STEEL SCREW (S)	44	46	48	50	52	54	56	58	60	62	64	66
19" DIA. STEEL SCREW (S)	46	48	50	52	54	56	58	60	62	64	66	68
20" DIA. STEEL SCREW (S)	48	50	52	54	56	58	60	62	64	66	68	70
21" DIA. STEEL SCREW (S)	50	52	54	56	58	60	62	64	66	68	70	72
22" DIA. STEEL SCREW (S)	52	54	56	58	60	62	64	66	68	70	72	74
23" DIA. STEEL SCREW (S)	54	56	58	60	62	64	66	68	70	72	74	76
24" DIA. STEEL SCREW (S)	56	58	60	62	64	66	68	70	72	74	76	78
25" DIA. STEEL SCREW (S)	58	60	62	64	66	68	70	72	74	76	78	80
26" DIA. STEEL SCREW (S)	60	62	64	66	68	70	72	74	76	78	80	82
27" DIA. STEEL SCREW (S)	62	64	66	68	70	72	74	76	78	80	82	84
28" DIA. STEEL SCREW (S)	64	66	68	70	72	74	76	78	80	82	84	86
29" DIA. STEEL SCREW (S)	66	68	70	72	74	76	78	80	82	84	86	88
30" DIA. STEEL SCREW (S)	68	70	72	74	76	78	80	82	84	86	88	90
31" DIA. STEEL SCREW (S)	70	72	74	76	78	80	82	84	86	88	90	92
32" DIA. STEEL SCREW (S)	72	74	76	78	80	82	84	86	88	90	92	94
33" DIA. STEEL SCREW (S)	74	76	78	80	82	84	86	88	90	92	94	96
34" DIA. STEEL SCREW (S)	76	78	80	82	84	86	88	90	92	94	96	98
35" DIA. STEEL SCREW (S)	78	80	82	84	86	88	90	92	94	96	98	100
36" DIA. STEEL SCREW (S)	80	82	84	86	88	90	92	94	96	98	100	102
37" DIA. STEEL SCREW (S)	82	84	86	88	90	92	94	96	98	100	102	104
38" DIA. STEEL SCREW (S)	84	86	88	90	92	94	96	98	100	102	104	106
39" DIA. STEEL SCREW (S)	86	88	90	92	94	96	98	100	102	104	106	108
40" DIA. STEEL SCREW (S)	88	90	92	94	96	98	100	102	104	106	108	110
41" DIA. STEEL SCREW (S)	90	92	94	96	98	100	102	104	106	108	110	112
42" DIA. STEEL SCREW (S)	92	94	96	98	100	102	104	106	108	110	112	114
43" DIA. STEEL SCREW (S)	94	96	98	100	102	104	106	108	110	112	114	116
44" DIA. STEEL SCREW (S)	96	98	100	102	104	106	108	110	112	114	116	118
45" DIA. STEEL SCREW (S)	98	100	102	104	106	108	110	112	114	116	118	120
46" DIA. STEEL SCREW (S)	100	102	104	106	108	110	112	114	116	118	120	122
47" DIA. STEEL SCREW (S)	102	104	106	108	110	112	114	116	118	120	122	124
48" DIA. STEEL SCREW (S)	104	106	108	110	112	114	116	118	120	122	124	126
49" DIA. STEEL SCREW (S)	106	108	110	112	114	116	118	120	122	124	126	128
50" DIA. STEEL SCREW (S)	108	110	112	114	116	118	120	122	124	126	128	130
51" DIA. STEEL SCREW (S)	110	112	114	116	118	120	122	124	126	128	130	132
52" DIA. STEEL SCREW (S)	112	114	116	118	120	122	124	126	128	130	132	134
53" DIA. STEEL SCREW (S)	114	116	118	120	122	124	126	128	130	132	134	136
54" DIA. STEEL SCREW (S)	116	118	120	122	124	126	128	130	132	134	136	138
55" DIA. STEEL SCREW (S)	118	120	122	124	126	128	130	132	134	136	138	140
56" DIA. STEEL SCREW (S)	120	122	124	126	128	130	132	134	136	138	140	142
57" DIA. STEEL SCREW (S)	122	124	126	128	130	132	134	136	138	140	142	144
58" DIA. STEEL SCREW (S)	124	126	128	130	132	134	136	138	140	142	144	146
59" DIA. STEEL SCREW (S)	126	128	130	132	134	136	138	140	142	144	146	148
60" DIA. STEEL SCREW (S)	128	130	132	134	136	138	140	142	144	146	148	150
61" DIA. STEEL SCREW (S)	130	132	134	136	138	140	142	144	146	148	150	152
62" DIA. STEEL SCREW (S)	132	134	136	138	140	142	144	146	148	150	152	154
63" DIA. STEEL SCREW (S)	134	136	138	140	142	144	146	148	150	152	154	156
64" DIA. STEEL SCREW (S)	136	138	140	142	144	146	148	150	152	154	156	158
65" DIA. STEEL SCREW (S)	138	140	142	144	146	148	150	152	154	156	158	160
66" DIA. STEEL SCREW (S)	140	142	144	146	148	150	152	154	156	158	160	162
67" DIA. STEEL SCREW (S)	142	144	146	148	150	152	154	156	158	160	162	164
68" DIA. STEEL SCREW (S)	144	146	148	150	152	154	156	158	160	162	164	166
69" DIA. STEEL SCREW (S)	146	148	150	152	154	156	158	160	162	164	166	168
70" DIA. STEEL SCREW (S)	148	150	152	154	156	158	160	162	164	166	168	170
71" DIA. STEEL SCREW (S)	150	152	154	156	158	160	162	164	166	168	170	172
72" DIA. STEEL SCREW (S)	152	154	156	158	160	162	164	166	168	170	172	174
73" DIA. STEEL SCREW (S)	154	156	158	160	162	164	166	168	170	172	174	176
74" DIA. STEEL SCREW (S)	156	158	160	162	164	166	168	170	172	174	176	178
75" DIA. STEEL SCREW (S)	158	160	162	164	166	168	170	172	174	176	178	180
76" DIA. STEEL SCREW (S)	160	162	164	166	168	170	172	174	176	178	180	182
77" DIA. STEEL SCREW (S)	162	164	166	168	170	172	174	176	178	180	182	184
78" DIA. STEEL SCREW (S)	164	166	168	170	172	174	176	178	180	182	184	186
79" DIA. STEEL SCREW (S)	166	168	170	172	174	176	178	180	182	184	186	188
80" DIA. STEEL SCREW (S)	168	170	172	174	176	178	180	182	184	186	188	190
81" DIA. STEEL SCREW (S)	170	172	174	176	178	180	182	184	186	188	190	192
82" DIA. STEEL SCREW (S)	172	174	176	178	180	182	184	186	188	190	192	194
83" DIA. STEEL SCREW (S)	174	176	178	180	182	184	186	188	190	192	194	196
84" DIA. STEEL SCREW (S)	176	178	180	182	184	186	188	190	192	194	196	198
85" DIA. STEEL SCREW (S)	178	180	182	184	186	188	190	192	194	196	198	200
86" DIA. STEEL SCREW (S)	180	182	184	186	188	190	192	194	196	198	200	202
87" DIA. STEEL SCREW (S)	182	184	186	188	190	192	194	196	198	200	202	204
88" DIA. STEEL SCREW (S)	184	186	188	190	192	194	196	198	200	202	204	206
89" DIA. STEEL SCREW (S)	186	188	190	192	194	196	198	200	202	204	206	208
90" DIA. STEEL SCREW (S)	188	190	192	194	196	198	200	202	204	206	208	210
91" DIA. STEEL SCREW (S)	190	192	194	196	198	200	202	204	206	208	210	212
92" DIA. STEEL SCREW (S)	192	194	196	198	200	202	204	206	208	210	212	214
93" DIA. STEEL SCREW (S)	194	196	198	200	202	204	206	208	210	212	214	216
94" DIA. STEEL SCREW (S)	196	198	200	202	204	206	208	210	212	214	216	218
95" DIA. STEEL SCREW (S)	198	200	202	204	206	208	210	212	214	216	218	220
96" DIA. STEEL SCREW (S)	200	202	204</									

MIAMI-DADE COUNTY, FLORIDA
 BUILDING CODE COMPLIANCE OFFICE (BCCO)
 PROJECT CONTROL DIVISION
NOTICE OF ACCEPTANCE (NOA)
 1070 Technology Drive,
 Nalanda, FL 33295

MIAMI-DADE COUNTY, FLORIDA
 140 WEST FLAGLER STREET, SUITE 1400
 MIAMI, FLORIDA 33130
 (305) 375-2600 FAX (305) 375-2608
 www.buildingcodeonline.com

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami-Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid for the application of the rules and regulations governing the use of construction materials in Miami-Dade County unless the AHJ (in areas other than Miami-Dade County) agrees to accept this product or material for use in its jurisdiction. This NOA is issued for quality assurance purposes. It is the manufacturer's responsibility to perform the tests and provide the test results to the AHJ. The manufacturer will bear the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

DESCRIPTION: Series "SGD-770" Aluminum Sliding Glass Doors w/ w Reinforcement
APPROVAL DOCUMENT: Drawing No. PGT0992, titled "Series 770 Alum SGD-LMI", sheets 1 through 23, prepared by PTC, LLC, dated 01/06/10, signed and sealed by Robert J. Amoruso, P.E., bearing the Miami-Dade County Product Control Approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: Large Missile Impact
 Listened:
 1. See table 1, 2 & 3, sheets 7, 8 & 9 of this approved drawing set the applicable SGD unit sizes, design conditions, reinforcement, glass types, sill and anchor requirements.

LABELING: Each unit shall have a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approval", unless otherwise noted herein.
REINFORCEMENT: This NOA shall be considered after a review of specifications has been filed and there has been no change to the applicable building code regarding the performance of this product.

TERMINATION: This NOA will occur after the expiration date or if there has been a revision or change in the product, use, or manufacturer of the product or process. Miami-Dade County will not be an endorser of any product, for sale, advertising or any other purpose shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.
ADVERTISING: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature, if any portion of the NOA is displayed, then it shall be done in its entirety.
INSTRUCTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributor and shall be available for inspection at the job site at the request of the Building Official.
 This NOA consists of this page 1 as well as evidence sheet E-1 and approval document mentioned above. The submitted documentation was reviewed by John J. Chasler, P.E.

NOTICE OF ACCEPTANCE - EVIDENCE SUBMITTED
 A. DRAWINGS
 1. Manufacturer's drawings and sections.
 2. Drawing No. PGT0992, titled "Series 770 Alum SGD-LMI", sheets 1 through 23, prepared by PTC, LLC, dated 01/06/10, signed and sealed by Robert J. Amoruso, P.E.
 B. TESTS
 1. Test reports on: 1) Air Infiltration Test, per TAS 301-94
 2) Uniform Static Air Pressure Test, per TAS 202-94
 3) Water Resistance Test, per TAS 202-94
 4) Forced Entry Test, per FBC 241.3.2 and TAS 202-94
 5) Large Missile Impact Test, per TAS 301-94
 6) Cyclonic Wind Pressure Loading, per TAS 203-94
 Along with marked-up drawings and installation diagrams of Aluminum Sliding Glass Doors, prepared by Fortification Testing Laboratory, Inc., Test Report No. FTI-5980, FTI-5993, FTI-6004, FTI-6011, FTI-6014, FTI-6015, FTI-6017, FTI-6021, FTI-6023, FTI-6024, FTI-6025, FTI-6026, FTI-6031, FTI-6033 and FTI-6034 dated 01/01/10, all signed and sealed by Julio Gonzalez, P.E.
 Note: The test reports No. FTI-5980, FTI-6011 and FTI-6015 have been reviewed and reissued on 12/03/09, signed and sealed by Julio Gonzalez, P.E.

C. CALCULATIONS
 1. And/or verification and comparative analysis dated 08/19/09, 12/03/09, 01/06/10 and last reviewed on 01/06/10, prepared by PTC, LLC, Robert J. Amoruso, P.E.
 2. Glazing complete with ASTM E-1304 0-04.
 D. QUALITY ASSURANCE
 1. Miami Dade Building Code Compliance Office (BCCO).

E. MATERIAL CERTIFICATIONS
 1. Notice of Acceptance No. 09-1114-04 issued to E. J. DuPont de Nemours & Co., Inc. for "DuPont SentryGrip 99" expiring on 01/17/2012.
 2. Notice of Acceptance No. 05-1208-02 issued to E. J. DuPont de Nemours, for "DuPont SentryGrip PVB" expiring on 12/17/2010.

F. STATEMENTS
 1. Statement letter of conformance and no financial interest, dated 08/19/09, signed by Robert J. Amoruso, P.E.
 2. Letter of Lab compliance, part of the above test reports.

G. OTHER
 1. Test proposals No. 09-0177, 0177-A & B approved by BCCO.

John J. Chasler, P.E.
 Director of Building Code Compliance
 Miami-Dade County
 140 West Flagler Street, Suite 1400
 Miami, Florida 33130
 Expired Date: February 17, 2015
 Approval Date: February 17, 2010
 Page: 1


NOA No. 09-0824-10
 Expired Date: February 17, 2015
 Approval Date: February 17, 2010
 Page: 1

GENERAL NOTES: SERIES 770 LMI SLIDING GLASS DOOR
 1. GLAZING TYPES OPTIONS (GLASS TYPES ARE FROM EXTERIOR TO INTERIOR)
 GLASS SIZES: 1" TEMPERED, 1/2" HEAT STRENGTHENED
 INTERLAYER TYPES: 05 = 050 DUREP; 06 = 060 DUREP; 07 = 070 DUREP; 08 = 080 DUREP; 09 = 090 DUREP; 10 = 100 DUREP; 11 = 110 DUREP; 12 = 120 DUREP; 13 = 130 DUREP; 14 = 140 DUREP; 15 = 150 DUREP; 16 = 160 DUREP; 17 = 170 DUREP; 18 = 180 DUREP; 19 = 190 DUREP; 20 = 200 DUREP; 21 = 210 DUREP; 22 = 220 DUREP; 23 = 230 DUREP; 24 = 240 DUREP; 25 = 250 DUREP; 26 = 260 DUREP; 27 = 270 DUREP; 28 = 280 DUREP; 29 = 290 DUREP; 30 = 300 DUREP; 31 = 310 DUREP; 32 = 320 DUREP; 33 = 330 DUREP; 34 = 340 DUREP; 35 = 350 DUREP; 36 = 360 DUREP; 37 = 370 DUREP; 38 = 380 DUREP; 39 = 390 DUREP; 40 = 400 DUREP; 41 = 410 DUREP; 42 = 420 DUREP; 43 = 430 DUREP; 44 = 440 DUREP; 45 = 450 DUREP; 46 = 460 DUREP; 47 = 470 DUREP; 48 = 480 DUREP; 49 = 490 DUREP; 50 = 500 DUREP; 51 = 510 DUREP; 52 = 520 DUREP; 53 = 530 DUREP; 54 = 540 DUREP; 55 = 550 DUREP; 56 = 560 DUREP; 57 = 570 DUREP; 58 = 580 DUREP; 59 = 590 DUREP; 60 = 600 DUREP; 61 = 610 DUREP; 62 = 620 DUREP; 63 = 630 DUREP; 64 = 640 DUREP; 65 = 650 DUREP; 66 = 660 DUREP; 67 = 670 DUREP; 68 = 680 DUREP; 69 = 690 DUREP; 70 = 700 DUREP; 71 = 710 DUREP; 72 = 720 DUREP; 73 = 730 DUREP; 74 = 740 DUREP; 75 = 750 DUREP; 76 = 760 DUREP; 77 = 770 DUREP; 78 = 780 DUREP; 79 = 790 DUREP; 80 = 800 DUREP; 81 = 810 DUREP; 82 = 820 DUREP; 83 = 830 DUREP; 84 = 840 DUREP; 85 = 850 DUREP; 86 = 860 DUREP; 87 = 870 DUREP; 88 = 880 DUREP; 89 = 890 DUREP; 90 = 900 DUREP; 91 = 910 DUREP; 92 = 920 DUREP; 93 = 930 DUREP; 94 = 940 DUREP; 95 = 950 DUREP; 96 = 960 DUREP; 97 = 970 DUREP; 98 = 980 DUREP; 99 = 990 DUREP; 100 = 1000 DUREP; 101 = 1010 DUREP; 102 = 1020 DUREP; 103 = 1030 DUREP; 104 = 1040 DUREP; 105 = 1050 DUREP; 106 = 1060 DUREP; 107 = 1070 DUREP; 108 = 1080 DUREP; 109 = 1090 DUREP; 110 = 1100 DUREP; 111 = 1110 DUREP; 112 = 1120 DUREP; 113 = 1130 DUREP; 114 = 1140 DUREP; 115 = 1150 DUREP; 116 = 1160 DUREP; 117 = 1170 DUREP; 118 = 1180 DUREP; 119 = 1190 DUREP; 120 = 1200 DUREP; 121 = 1210 DUREP; 122 = 1220 DUREP; 123 = 1230 DUREP; 124 = 1240 DUREP; 125 = 1250 DUREP; 126 = 1260 DUREP; 127 = 1270 DUREP; 128 = 1280 DUREP; 129 = 1290 DUREP; 130 = 1300 DUREP; 131 = 1310 DUREP; 132 = 1320 DUREP; 133 = 1330 DUREP; 134 = 1340 DUREP; 135 = 1350 DUREP; 136 = 1360 DUREP; 137 = 1370 DUREP; 138 = 1380 DUREP; 139 = 1390 DUREP; 140 = 1400 DUREP; 141 = 1410 DUREP; 142 = 1420 DUREP; 143 = 1430 DUREP; 144 = 1440 DUREP; 145 = 1450 DUREP; 146 = 1460 DUREP; 147 = 1470 DUREP; 148 = 1480 DUREP; 149 = 1490 DUREP; 150 = 1500 DUREP; 151 = 1510 DUREP; 152 = 1520 DUREP; 153 = 1530 DUREP; 154 = 1540 DUREP; 155 = 1550 DUREP; 156 = 1560 DUREP; 157 = 1570 DUREP; 158 = 1580 DUREP; 159 = 1590 DUREP; 160 = 1600 DUREP; 161 = 1610 DUREP; 162 = 1620 DUREP; 163 = 1630 DUREP; 164 = 1640 DUREP; 165 = 1650 DUREP; 166 = 1660 DUREP; 167 = 1670 DUREP; 168 = 1680 DUREP; 169 = 1690 DUREP; 170 = 1700 DUREP; 171 = 1710 DUREP; 172 = 1720 DUREP; 173 = 1730 DUREP; 174 = 1740 DUREP; 175 = 1750 DUREP; 176 = 1760 DUREP; 177 = 1770 DUREP; 178 = 1780 DUREP; 179 = 1790 DUREP; 180 = 1800 DUREP; 181 = 1810 DUREP; 182 = 1820 DUREP; 183 = 1830 DUREP; 184 = 1840 DUREP; 185 = 1850 DUREP; 186 = 1860 DUREP; 187 = 1870 DUREP; 188 = 1880 DUREP; 189 = 1890 DUREP; 190 = 1900 DUREP; 191 = 1910 DUREP; 192 = 1920 DUREP; 193 = 1930 DUREP; 194 = 1940 DUREP; 195 = 1950 DUREP; 196 = 1960 DUREP; 197 = 1970 DUREP; 198 = 1980 DUREP; 199 = 1990 DUREP; 200 = 2000 DUREP; 201 = 2010 DUREP; 202 = 2020 DUREP; 203 = 2030 DUREP; 204 = 2040 DUREP; 205 = 2050 DUREP; 206 = 2060 DUREP; 207 = 2070 DUREP; 208 = 2080 DUREP; 209 = 2090 DUREP; 210 = 2100 DUREP; 211 = 2110 DUREP; 212 = 2120 DUREP; 213 = 2130 DUREP; 214 = 2140 DUREP; 215 = 2150 DUREP; 216 = 2160 DUREP; 217 = 2170 DUREP; 218 = 2180 DUREP; 219 = 2190 DUREP; 220 = 2200 DUREP; 221 = 2210 DUREP; 222 = 2220 DUREP; 223 = 2230 DUREP; 224 = 2240 DUREP; 225 = 2250 DUREP; 226 = 2260 DUREP; 227 = 2270 DUREP; 228 = 2280 DUREP; 229 = 2290 DUREP; 230 = 2300 DUREP; 231 = 2310 DUREP; 232 = 2320 DUREP; 233 = 2330 DUREP; 234 = 2340 DUREP; 235 = 2350 DUREP; 236 = 2360 DUREP; 237 = 2370 DUREP; 238 = 2380 DUREP; 239 = 2390 DUREP; 240 = 2400 DUREP; 241 = 2410 DUREP; 242 = 2420 DUREP; 243 = 2430 DUREP; 244 = 2440 DUREP; 245 = 2450 DUREP; 246 = 2460 DUREP; 247 = 2470 DUREP; 248 = 2480 DUREP; 249 = 2490 DUREP; 250 = 2500 DUREP; 251 = 2510 DUREP; 252 = 2520 DUREP; 253 = 2530 DUREP; 254 = 2540 DUREP; 255 = 2550 DUREP; 256 = 2560 DUREP; 257 = 2570 DUREP; 258 = 2580 DUREP; 259 = 2590 DUREP; 260 = 2600 DUREP; 261 = 2610 DUREP; 262 = 2620 DUREP; 263 = 2630 DUREP; 264 = 2640 DUREP; 265 = 2650 DUREP; 266 = 2660 DUREP; 267 = 2670 DUREP; 268 = 2680 DUREP; 269 = 2690 DUREP; 270 = 2700 DUREP; 271 = 2710 DUREP; 272 = 2720 DUREP; 273 = 2730 DUREP; 274 = 2740 DUREP; 275 = 2750 DUREP; 276 = 2760 DUREP; 277 = 2770 DUREP; 278 = 2780 DUREP; 279 = 2790 DUREP; 280 = 2800 DUREP; 281 = 2810 DUREP; 282 = 2820 DUREP; 283 = 2830 DUREP; 284 = 2840 DUREP; 285 = 2850 DUREP; 286 = 2860 DUREP; 287 = 2870 DUREP; 288 = 2880 DUREP; 289 = 2890 DUREP; 290 = 2900 DUREP; 291 = 2910 DUREP; 292 = 2920 DUREP; 293 = 2930 DUREP; 294 = 2940 DUREP; 295 = 2950 DUREP; 296 = 2960 DUREP; 297 = 2970 DUREP; 298 = 2980 DUREP; 299 = 2990 DUREP; 300 = 3000 DUREP; 301 = 3010 DUREP; 302 = 3020 DUREP; 303 = 3030 DUREP; 304 = 3040 DUREP; 305 = 3050 DUREP; 306 = 3060 DUREP; 307 = 3070 DUREP; 308 = 3080 DUREP; 309 = 3090 DUREP; 310 = 3100 DUREP; 311 = 3110 DUREP; 312 = 3120 DUREP; 313 = 3130 DUREP; 314 = 3140 DUREP; 315 = 3150 DUREP; 316 = 3160 DUREP; 317 = 3170 DUREP; 318 = 3180 DUREP; 319 = 3190 DUREP; 320 = 3200 DUREP; 321 = 3210 DUREP; 322 = 3220 DUREP; 323 = 3230 DUREP; 324 = 3240 DUREP; 325 = 3250 DUREP; 326 = 3260 DUREP; 327 = 3270 DUREP; 328 = 3280 DUREP; 329 = 3290 DUREP; 330 = 3300 DUREP; 331 = 3310 DUREP; 332 = 3320 DUREP; 333 = 3330 DUREP; 334 = 3340 DUREP; 335 = 3350 DUREP; 336 = 3360 DUREP; 337 = 3370 DUREP; 338 = 3380 DUREP; 339 = 3390 DUREP; 340 = 3400 DUREP; 341 = 3410 DUREP; 342 = 3420 DUREP; 343 = 3430 DUREP; 344 = 3440 DUREP; 345 = 3450 DUREP; 346 = 3460 DUREP; 347 = 3470 DUREP; 348 = 3480 DUREP; 349 = 3490 DUREP; 350 = 3500 DUREP; 351 = 3510 DUREP; 352 = 3520 DUREP; 353 = 3530 DUREP; 354 = 3540 DUREP; 355 = 3550 DUREP; 356 = 3560 DUREP; 357 = 3570 DUREP; 358 = 3580 DUREP; 359 = 3590 DUREP; 360 = 3600 DUREP; 361 = 3610 DUREP; 362 = 3620 DUREP; 363 = 3630 DUREP; 364 = 3640 DUREP; 365 = 3650 DUREP; 366 = 3660 DUREP; 367 = 3670 DUREP; 368 = 3680 DUREP; 369 = 3690 DUREP; 370 = 3700 DUREP; 371 = 3710 DUREP; 372 = 3720 DUREP; 373 = 3730 DUREP; 374 = 3740 DUREP; 375 = 3750 DUREP; 376 = 3760 DUREP; 377 = 3770 DUREP; 378 = 3780 DUREP; 379 = 3790 DUREP; 380 = 3800 DUREP; 381 = 3810 DUREP; 382 = 3820 DUREP; 383 = 3830 DUREP; 384 = 3840 DUREP; 385 = 3850 DUREP; 386 = 3860 DUREP; 387 = 3870 DUREP; 388 = 3880 DUREP; 389 = 3890 DUREP; 390 = 3900 DUREP; 391 = 3910 DUREP; 392 = 3920 DUREP; 393 = 3930 DUREP; 394 = 3940 DUREP; 395 = 3950 DUREP; 396 = 3960 DUREP; 397 = 3970 DUREP; 398 = 3980 DUREP; 399 = 3990 DUREP; 400 = 4000 DUREP; 401 = 4010 DUREP; 402 = 4020 DUREP; 403 = 4030 DUREP; 404 = 4040 DUREP; 405 = 4050 DUREP; 406 = 4060 DUREP; 407 = 4070 DUREP; 408 = 4080 DUREP; 409 = 4090 DUREP; 410 = 4100 DUREP; 411 = 4110 DUREP; 412 = 4120 DUREP; 413 = 4130 DUREP; 414 = 4140 DUREP; 415 = 4150 DUREP; 416 = 4160 DUREP; 417 = 4170 DUREP; 418 = 4180 DUREP; 419 = 4190 DUREP; 420 = 4200 DUREP; 421 = 4210 DUREP; 422 = 4220 DUREP; 423 = 4230 DUREP; 424 = 4240 DUREP; 425 = 4250 DUREP; 426 = 4260 DUREP; 427 = 4270 DUREP; 428 = 4280 DUREP; 429 = 4290 DUREP; 430 = 4300 DUREP; 431 = 4310 DUREP; 432 = 4320 DUREP; 433 = 4330 DUREP; 434 = 4340 DUREP; 435 = 4350 DUREP; 436 = 4360 DUREP; 437 = 4370 DUREP; 438 = 4380 DUREP; 439 = 4390 DUREP; 440 = 4400 DUREP; 441 = 4410 DUREP; 442 = 4420 DUREP; 443 = 4430 DUREP; 444 = 4440 DUREP; 445 = 4450 DUREP; 446 = 4460 DUREP; 447 = 4470 DUREP; 448 = 4480 DUREP; 449 = 4490 DUREP; 450 = 4500 DUREP; 451 = 4510 DUREP; 452 = 4520 DUREP; 453 = 4530 DUREP; 454 = 4540 DUREP; 455 = 4550 DUREP; 456 = 4560 DUREP; 457 = 4570 DUREP; 458 = 4580 DUREP; 459 = 4590 DUREP; 460 = 4600 DUREP; 461 = 4610 DUREP; 462 = 4620 DUREP; 463 = 4630 DUREP; 464 = 4640 DUREP; 465 = 4650 DUREP; 466 = 4660 DUREP; 467 = 4670 DUREP; 468 = 4680 DUREP; 469 = 4690 DUREP; 470 = 4700 DUREP; 471 = 4710 DUREP; 472 = 4720 DUREP; 473 = 4730 DUREP; 474 = 4740 DUREP; 475 = 4750 DUREP; 476 = 4760 DUREP; 477 = 4770 DUREP; 478 = 4780 DUREP; 479 = 4790 DUREP; 480 = 4800 DUREP; 481 = 4810 DUREP; 482 = 4820 DUREP; 483 = 4830 DUREP; 484 = 4840 DUREP; 485 = 4850 DUREP; 486 = 4860 DUREP; 487 = 4870 DUREP; 488 = 4880 DUREP; 489 = 4890 DUREP; 490 = 4900 DUREP; 491 = 4910 DUREP; 492 = 4920 DUREP; 493 = 4930 DUREP; 494 = 4940 DUREP; 495 = 4950 DUREP; 496 = 4960 DUREP; 497 = 4970 DUREP; 498 = 4980 DUREP; 499 = 4990 DUREP; 500 = 5000 DUREP; 501 = 5010 DUREP; 502 = 5020 DUREP; 503 = 5030 DUREP; 504 = 5040 DUREP; 505 = 5050 DUREP; 506 = 5060 DUREP; 507 = 5070 DUREP; 508 = 5080 DUREP; 509 = 5090 DUREP; 510 = 5100 DUREP; 511 = 5110 DUREP; 512 = 5120 DUREP; 513 = 5130 DUREP; 514 = 5140 DUREP; 515 = 5150 DUREP; 516 = 5160 DUREP; 517 = 5170 DUREP; 518 = 5180 DUREP; 519 = 5190 DUREP; 520 = 5200 DUREP; 521 = 5210 DUREP; 522 = 5220 DUREP; 523 = 5230 DUREP; 524 = 5240 DUREP; 525 = 5250 DUREP; 526 = 5260 DUREP; 527 = 5270 DUREP; 528 = 5280 DUREP; 529 = 5290 DUREP; 530 = 5300 DUREP; 531 = 5310 DUREP; 532 = 5320 DUREP; 533 = 5330 DUREP; 534 = 5340 DUREP; 535 = 5350 DUREP; 536 = 5360 DUREP; 537 = 5370 DUREP; 538 = 5380 DUREP; 539 = 5390 DUREP; 540 = 5400 DUREP; 541 = 5410 DUREP; 542 = 5420 DUREP; 543 = 5430 DUREP; 544 = 5440 DUREP; 545 = 5450 DUREP; 546 = 5460 DUREP; 547 = 5470 DUREP; 548 = 5480 DUREP; 549 = 5490 DUREP; 550 = 5500 DUREP; 551 = 5510 DUREP; 552 = 5520 DUREP; 553 = 5530 DUREP; 554 = 5540 DUREP; 555 = 5550 DUREP; 556 = 5560 DUREP; 557 = 5570 DUREP; 558 = 5580 DUREP; 559 = 5590 DUREP; 560 = 5600 DUREP; 561 = 5610 DUREP; 562 = 5620 DUREP; 563 = 5630 DUREP; 564 = 5640 DUREP; 565 = 5650 DUREP; 566 = 5660 DUREP; 567 = 5670 DUREP; 568 = 5680 DUREP; 569 = 5690 DUREP; 570 = 5700 DUREP; 571 = 5710 DUREP; 572 = 5720 DUREP; 573 = 5730 DUREP; 574 = 5740 DUREP; 575 = 5750 DUREP; 576 = 5760 DUREP; 577 = 5770 DUREP; 578 = 5780 DUREP; 579 = 5790 DUREP; 580 = 5800 DUREP; 581 = 5810 DUREP; 582 = 5820 DUREP; 583 = 5830 DUREP; 584 = 5840 DUREP; 585 = 5850 DUREP; 586 = 5860 DUREP; 587 = 5870 DUREP; 588 = 5880 DUREP; 589 = 5890 DUREP; 590 = 5900 DUREP; 591 = 5910 DUREP; 592 = 5920 DUREP; 593 = 5930 DUREP; 594 = 5940 DUREP; 595 = 5950 DUREP; 596 = 5960 DUREP; 597 = 5970 DUREP; 598 = 5980 DUREP; 599 = 5990 DUREP; 600 = 6000 DUREP; 601 = 6010 DUREP; 602 = 6020 DUREP; 603 = 6030 DUREP; 604 = 6040 DUREP; 605 = 6050 DUREP; 606 = 6060 DUREP; 607 = 6070 DUREP; 608 = 6080 DUREP; 609 = 6090 DUREP; 610 = 6100 DUREP; 611 = 6110 DUREP; 612 = 6120 DUREP; 613 = 6130 DUREP; 614 = 6140 DUREP; 615 = 6150 DUREP; 616 = 6160 DUREP; 617 = 6170 DUREP; 618 = 6180 DUREP; 619 = 6190 DUREP; 620 = 6200 DUREP; 621 = 6210 DUREP; 622 = 6220 DUREP; 623 = 6230 DUREP; 624 = 6240 DUREP; 625 = 6250 DUREP; 626 = 6260 DUREP; 627 = 6270 DUREP; 628 = 6280 DUREP; 629 = 6290 DUREP; 630 = 6300 DUREP; 631 = 6310 DUREP; 632 = 6320 DUREP; 633 = 6330 DUREP; 634 = 6340 DUREP; 635 = 6350 DUREP; 636 = 6360 DUREP; 637 = 6370 DUREP; 638 = 6380 DUREP; 639 = 6390 DUREP; 640 = 6400 DUREP; 641 = 6410 DUREP; 642 = 6420 DUREP; 643 = 6430 DUREP; 644 = 6440 DUREP; 645 = 6450 DUREP; 646 = 6460 DUREP; 647 = 6470 DUREP; 648 = 6480 DUREP; 649 = 6490 DUREP; 650 = 6500 DUREP; 651 = 6510 DUREP; 652 = 6520 DUREP; 653 = 6530 DUREP; 654 = 6540 DUREP; 655 = 6550 DUREP; 656 = 6560 DUREP; 657 = 6570 DUREP; 658 = 6580 DUREP; 659 = 6590 DUREP; 660 = 6600 DUREP; 661 = 6610 DUREP; 662 = 6620 DUREP; 663 = 6630 DUREP; 664 = 6640 DUREP; 665 = 6650 DUREP; 666 = 6660 DUREP; 667 = 6670 DUREP; 668 = 6680 DUREP; 669 = 6690 DUREP; 670 = 6700 DUREP; 671 = 6710 DUREP; 672 = 6720 DUREP; 673 = 6730 DUREP; 674 = 6740 DUREP; 675 = 6750 DUREP; 676 = 6760 DUREP; 677 = 6770 DUREP; 678 = 6780 DUREP; 679 = 6790 DUREP; 680 = 6800 DUREP; 681 = 6810 DUREP; 682 = 6820 DUREP; 683 = 6830 DUREP; 684 = 6840 DUREP; 685 = 6850 DUREP; 686 = 6860 DUREP; 687 = 6870 DUREP; 688 = 6880 DUREP; 689 = 6890 DUREP; 690 = 6900 DUREP; 691 = 6910 DUREP; 692 = 6920 DUREP; 693 = 6930 DUREP; 694 = 6940 DUREP; 695 = 6950 DUREP; 696 = 6960 DUREP; 697 = 6970 DUREP; 698 = 6980 DUREP; 699 = 6990 DUREP; 700 = 7000 DUREP; 701 = 7010 DUREP; 702 = 7020 DUREP; 703 = 7030 DUREP; 704 = 7040 DUREP; 705 = 7050 DUREP; 706 = 7060 DUREP; 707 = 7070 DUREP; 708 = 7080 DUREP; 709 = 7090 DUREP; 710 = 7100 DUREP; 711 = 7110 DUREP; 712 = 7120 DUREP; 713 = 7130 DUREP; 714 = 7140 DUREP; 715 = 7150 DUREP; 716 = 7160 DUREP; 717 = 7170 DUREP;


U.S. GENERAL NOTES

- HILES:** Holes are by others unless otherwise indicated. Fields cut holes thru the units may not cut prestressed strands without prior written approval from Pre-Cast Specialties Inc. Engineering Department.
- VERTICAL RISERS:** The general contractor shall insure that vertical risers, etc., do not interfere with placement of Hollow Core units.
- HANDLING:** Hollow Core units may not be lifted by inserting hooks, bars or other lifting devices into the voids, and may not be inverted. Hollow Core units must be lifted 1'-0" from the end only.
- DIMENSIONS AND DETAILS:** The customer and/or his agent will be responsible for all dimension and details taken from the contract drawings and shown hereon. PCSI will not be responsible for any changes made after approval of these drawings.
- ROOF UNITS:** Slight vertical movement of precast concrete roof units is anticipated but can be reduced by proper insulation. PCSI recommends a physical separation of the plaster at the intersection of non-bearing walls and ceilings.
- CAMBER:** Camber is an inherent condition in all prestressed flexural members and the general contractor shall make allowances for same. If additional thickness of topping is needed for leveling purposes, contact our engineering department for approval. Highest estimated camber at time of erection: 3/8"
- CONCRETE:** Strength of concrete shall be a minimum of 6000 psi at 28 days. Structural topping where specified shall be of 4000 psi 28 day strength concrete, reinforced with 6 x 6 = 10/10 welded wire mesh. The thickness of such topping shall be a minimum of 2 inches at the center of the span and may vary due to camber or deflection from the center to the supports as required for a level surface. The topping pour and all materials required same are by others.
- GROUTING:** All joints between slabs shall be fully packed with a pourable grout consisting of 1 part Portland Cement to 3 parts clean sand. The grouted deck shall be allowed to cure before removing any leveling shores, cutting any holes or applying any further construction loads. THE OPERATION OF GROUTING THE HOLLOW CORE SLABS KEYWAYS MUST BE PERFORMED REGARDLESS OF ANY TOPPING BEING APPLIED TO HOLLOW CORE SLABS.
- PRESTRESSED STRANDS:** Strands to be 7 wire, 3/8" dia., tensioned to 13800 lbs. each for 3'-4" planks. (7 wire, 1/2" dia., tensioned to 28900 lbs. for 4'-0" planks). The number of strands are indicated by the first two digits following the letter HC or US in the designation.
- TOLERANCES:**


Width	Full Width Units	± 1/4"	Length	± 1"
	Saw Cut Units	± 1/2"	Thickness	± 1/4"
	Split Units	± 1 1/2"	Deviation From Square	± 1"
- DESIGN LOADS:**
SECOND FLOOR: 8" U.S. W/65 P.S.F. (L.L.=40 P.S.F. + D.L.=25 P.S.F.) & ± 2" TOPPING
- Minor cracking (hairline and tension) will occur in precast/prestressed concrete created by shrinkage of concrete and temporary loads during production, transportation or erection without being structurally detrimental to the units. These cracks have no structural significance and does not affect durability of these units. Cracking should not be cause for rejection, when properly repaired.
- FIRE RESISTANCE:** All Precast/Prestressed concrete products shown on these shop drawings have a maximum fire resistance of one (1) hour, unless indicated otherwise.
- All Precast/Prestressed concrete products shown on these shop drawings are structural quality, any rework/finishing necessary for final architectural appearance is by others.
- TIE BEAMS:** Tie beams must be true, level and free of knots. If precast perimeter beams or knockout blocks are used, they must be COMPLETELY FILLED.
- ACCESS:** General Contractor agrees to provide and maintain for the duration of precast installation, stabilized access, acceptable to PCSI so trucks and cranes can move under their own power to various points of erection with no overhead obstruction. Customer accepts all liability for deliveries beyond the curb line, including all underground utilities and cost for loss of time. PCSI reserves the right to stop deliveries and/or erection in the event such conditions are not provided.
- THIS SYMBOL INDICATES SAWCUT OR SPLIT EDGE OF HOLLOW CORE PLANKS.
- WHERE STRUCTURAL TOPPING IS TO BE APPLIED, PLANKS ARE TO BE THOROUGHLY CLEANED AND PREPARED BY G.C. PRIOR TO TOPPING TO INSURE ADEQUATE BOND STRENGTH.
- TIE BEAMS MUST BE TRUE, LEVEL AND FREE OF KNOTS. IF PRECAST PERIMETER BEAMS OR KNOCKOUT BLOCKS ARE USED, THEY MUST BE COMPLETELY FILLED.
- ALL NON BEARING WALLS SHOULD BE HELD DOWN 1" UNTIL SLABS ARE SET AND GROUTED AND ALL DEAD LOADS ARE APPLIED TO THE SLABS BEFORE DRY PACKING THE GAP BETWEEN THE NON BEARING WALL AND THE SLAB.
- Dowels must be placed in the beams in a manner to allow the proper bearing of our product as detailed in our different sections. Non compliance with this item may delay the erection of these product with additional cost to the General Contractor.




SECTION 1 SCALE: 3/4" = 1'-0"




SECTION 2 SCALE: 3/4" = 1'-0"




SECTION 3 SCALE: 3/4" = 1'-0"




SECTION 4 SCALE: 3/4" = 1'-0"







SECTION 5 SCALE: 3/4" = 1'-0"




SECTION 6 SCALE: 3/4" = 1'-0"



SECTION 7 SCALE: 3/4" = 1'-0"



APPROVED DRAWINGS



APPROVED
VOID
MAY - 7 2012
CITY OF HOLLYWOOD, FLA.
STRUCTURAL


ALLOWABLE LOADS			HOLLOW CORE (US) SCHEDULE					
with Topp.	no Topp.	REV.	MARK	UNIT	No Required	LENGTH	WIDTH	REMARKS
65		△	9	8"US-038	4	18'-7"	4'-0"	-
			9A	8"US-038	1	18'-7"	2'-9 1/2"	SAWCUT
			10	8"US-038	7	16'-1"	4'-0"	-
			11	8"US-038	4	18'-11"	4'-0"	-
			12	8"US-038	2	16'-3 1/2"	4'-0"	-
			12A	8"US-038	1	16'-3 1/2"	2'-3 1/2"	SAWCUT
			12B	8"US-038	1	16'-3 1/2"	4'-0"	W/C.O.
			13A	8"US-038	1	8'-5"	1'-8"	SAWCUT
			14A	8"US-048	2	22'-4"	2'-1"	SAWCUT
			15	8"US-038	2	13'-5"	4'-0"	-
			15A	8"US-038	1	13'-5"	2'-1 1/2"	SAWCUT
			16A	8"US-038	1	15'-9 1/2"	4'-0"	W/C.O.
			16B	8"US-038	1	15'-9 1/2"	2'-9 1/2"	SAWCUT
			16C	8"US-038	1	15'-9 1/2"	2'-3 1/2"	SAWCUT
			117	8"US-038	1	18'-2"	4'-0"	1'-11" CANT. ONE END
			117A	8"US-038	1	18'-2"	2'-10"	1'-11" CANT. ONE END-SAWCUT
			117B	8"US-038	1	18'-2"	2'-10"	1'-11" CANT. ONE END-SAWCUT

SCHEDULE / SECTIONS & GENERAL NOTES

DATE	DESCRIPTION	BY	ENGR.	DATE	SEAL
04/02/12	CHANGE 4" H.C. TO POUR IN PLACE (BY G.C.)	J.C.			

PROJECT: SULLIVAN RESIDENCE
1128 NORTH NORTHLAKE DR. HOLLYWOOD, FL.
ONTR.: BARRON DEVELOPMENT
TEL.: (954) 749-7295

PRE-CAST/PRESTRESS ENGR.
JOHN P. MCGREW, P.E.
FLORIDA P.E. NO. 26641
APPROVED DATE: 04/06/12 SHEET NO. 1 WO#: P-12-5649
Pre-Cast Specialties, Inc.
1380 N.E. 48th St. Pompano Beach, FL. 33064
PHONE: 1-800-749-4041 FAX: 954-781-1194



SUB T - PLAN
 APPROVED FOR THE CITY

SECOND FLOOR FRAMING PLAN
 SCALE: 3/16"=1'-0"

8" U.S. W/65 P.S.F.
 & ± 2" TOPPING

APPROVED
 MAY - 7 2012
 CITY OF HOLLYWOOD, FL.
 STRUCTURAL

2nd. FLOOR

PRE-CAST/PRESTRESS ENGR.
 JOHN P. MCGREW, P.E.
 FLORIDA P.E. NO: 28641

DATE	DESCRIPTION	BY	ENGR.	DATE	SEAL
04/02/12	4" H.C. CHANGE TO POUR IN PLACE BY G.C.	J.C.	S.M.	04/09/12	
			J.C.	03/22/12	

PROJECT:
SULLIVAN RESIDENCE
 1128 NORTH NORTHLAKE DR. HOLLYWOOD, FL.
 CONTR: BARRON DEVELOPMENT
 TEL.: (954) 749-7295

APPROVED DATE: 04/08/12
 SHEET NO.: 2
 WO#: P-12-5649

PCSI
 Pre-Cast Specialties, Inc.
 1380 N.E. 48th St. Pompano Beach, FL 33064
 PHONE: 1-800-749-4041 FAX: 954-781-1194

